

HAZARD RATING

4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

MATERIAL SAFETY DATA SHEET
VEXCON NO. CC118



Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA 19135

VOICE: 215.332.7709 • FAX: 215.332.9997

TOLL FREE: 888-VEXCON-1

WEBSITE ADDRESS: www.vexcon.com

GENERAL INFORMATION

PRODUCT IDENTIFICATION: CERTI-VEX ENVIO® CURE CLEAR 1315, VOC

VOC CONTENT: 285 GRAMS/LITER OR 2.38 #/GAL.

CATEGORY: CURE AND SEAL

COMMON NAME: ALPHA METHYL STYRENE EMULSION

DOT SHIPPING NAME: IN CONTAINERS LESS THAN 119 GALS AND CONTAINERS GREATER THAN 119 GALS: CERTI-VEX ENVIOCURE CLEAR 1315, VOC (NON-REGULATED)

HEALTH AND SAFETY: COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION: DO NOT INDUCE VOMITING IF SWALLOWED: KEEP FROM FREEZING USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT.

SECTION I

MANUFACTURER: VEXCON CHEMICALS
EMERGENCY NO.: 1-800-858-2828
CHEMTREC NO.: 1-800-424-9300
TELEPHONE NO.: 1-215-332-7709
ADDRESS: 7240 STATE RD., PHILA., PA 19135
PREPARED: AUGUST 1998
UPDATED: JANUARY 2003
PREPARED BY: DARRYL F. MANUEL

SECTION II HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS. NO.	%	HAZARD DATA	UN#
TITANIUM DIOXIDE	13463-67-7		10 mg/M ³ , Total Dust	
CALCIUM CARBONATE	1317-65-3		15 mg/M ³ , Total Dust 5 mg/M ³ , Respirable Dust	
AR100 SOLVENT	64742-95-6		TLV 50 ppm	1268
EMULSIFIERS/ADDITIVES		3%	ND	
WATER		62%	NA	
ALPHA METHYL STYRENE POLYMER	9011-11-4	35%	ND	

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 212 F **MELTING POINT:** N/A
VAPOR PRESSURE: 2.00 mm Hg **SPECIFIC GRAVITY (H2O=1):** 1.01
VAPOR DENSITY (AIR=1): GREATER THAN AIR
SOLUBILITY IN H2O BY WT: 100% **% VOLATILES BY VOL:** 78%
EVAPORATION RATE (ETHER 1): LESS THAN
APPEARANCE AND ODOR: MILKY EMULSION
PH (AS IS): 8-9 **pH (1% SOLN):** ND

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: (TEST METHOD) >200 F TCC
AUTOIGNITION TEMP: N.D. **LOWER:** N.D. **UPPER:** N.D.
FLAMMABLE LIMITS IN AIR, % BY VOL:
EXTINGUISHING MEDIA: WATER, FOAM
SPECIAL FIRE FIGHTING PROCEDURES: NONE
UNUSUAL FIRE AND EXPLOSION HAZARD: PRODUCT WILL BURN IF TEMPERATURE EXCEEDS BOILING POINT OF WATER MIX UNDER SOME CONDITIONS. NO UNUSUAL HAZARDS.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: THIS PRODUCT IS STABLE
INCOMPATIBILITY: THIS PRODUCT IS INCOMPATIBLE WITH STRONG ACIDS.
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION IN THE PRESENCE OF AIR YIELDS CARBON MONOXIDE AND/OR CARBON DIOXIDE.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: N/A

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

ALL INFORMATION IS FOR ODORLESS MINERAL SPIRITS

ROUTES OF EXPOSURE:

INHALATION: VAPOR INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA OR HEADACHE.

SKIN CONTACT: PROLONGED OR REPEATED CONTACT CAN RESULT IN MODERATE IRRITATION

SKIN ABSORPTION: PROLONGED OR REPEATED CONTACT CAN RESULT IN MODERATE IRRITATION

EYE CONTACT: THIS PRODUCT CAN CAUSE SEVERE IRRITATION.

INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING.

EFFECTS OF OVEREXPOSURE: ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.

ACUTE OVEREXPOSURE: PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CONSULT WITH A PHYSICIAN.

SKIN: IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SEEK PROMPT MEDICAL ATTENTION.

- **FOR USE BY PROFESSIONAL APPLICATORS ONLY.**

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

WASTE DISPOSAL METHOD: TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA OR STATE REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT. TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LANDFILL SITES ARE AVAILABLE.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR

SPILLED: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOTLIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN UP IS COMPLETE. STOP SPILL AT SOURCE. DIKE SPILL AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE: FULLFACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYE: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER CLOTHING MUST BE WASHED/DRIED BEFORE RE-USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

OTHER HANDLING AND STORAGE REQUIREMENTS: STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMIS HAZARD RATINGS:

	NPCA-HMIS	NFPA 704	KEY
HEALTH	1	1	4=SEVERE
FLAMMABILITY	1	1	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT
			0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER).

FEDERAL:

FDA:

USDA:

TSCA: THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY: DARRYL MANUEL
TITLE: PRESIDENT
COMPANY: VEXCON CHEMICALS
ADDRESS: 7240 STATE ROAD. PHILA., PA 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETION OF THE INFORMATION CONTAINED HEREIN