

**HAZARD RATING**

4=EXTREME  
 3=HIGH  
 2=MODERATE  
 1=SLIGHT  
 0=INSIGNIFICANT

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>REACTIVITY</b>	<b>0</b>

**MATERIAL SAFETY DATA SHEET**  
**VEXCON NO. CP102- PART B**



Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA 19135  
 VOICE: 215.332.7709 • FAX: 215.332.9997  
 TOLL FREE: 888-VEXCON-1  
 WEBSITE ADDRESS: [www.vexcon.com](http://www.vexcon.com)

**GENERAL INFORMATION**

**PRODUCT IDENTIFICATION:** VEXCON POWERCOAT® SEISMIC GROUT  
 PART B  
**VOC CONTENT:** 254 GR./LITER 2.12 OR #/GAL.  
**CATEGORY:** INDUSTRIAL MAINTENANCE COATING  
**COMMON NAME:** EPOXY GROUT  
**DOT SHIPPING NAME:** IN CONTAINERS LESS THAN 119 GALS AND  
 CONTAINERS GREATER THAN 119 GALS: POWERCOAT SEISMIC GROUT  
 PART B (NON-REGULATED) VOC: MEETS ALL REQUIREMENTS  
**FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:** RQ (ACETONE)  
 RESIN SOLUTION, FLAMMABLE, 3, UN1866, III

**SECTION I**

**MANUFACTURER:** VEXCON CHEMICALS  
**ADDRESS:** 7240 STATE RD.,PHILA.,PA 19135  
**EMERGENCY NO.:** 1-800-858-2828  
**TELEPHONE NO.:** 1-215-332-7709  
**CHEMTREC NO.:** 1-800-424-9300  
**PREPARED:** JANUARY 2006  
**PREPARED BY:** Darryl F. Manuel /President

**SECTION II HAZARDOUS INGREDIENTS**

<b>MATERIAL OR COMPONENT</b>	<b>CAS NO.</b>	<b>%</b>	<b>HAZARD LIMITS</b>	<b>UN#</b>
BISPHENOL A/EPICHLOROHYDRIN				
EPOXY RESIN	25068-38-6	79	.88%	ND
AR 100 SOLVENT	64742-95-6		12%	TLV 50 PPM 1255
WHICH CONTAINS				OSHA HAZARD: COMBUSTIBLE
HYDROCARBONS				NOT ESTABLISHED
1,2,4 TRIMETHLBENZENE				OSHA PEL: ACGIH TLV/TWA 25 ppm
XYLENE				OSHA PEL: ACGIH TLV/TWA 100 ppm
CUMENE				OSHA PEL: ACGIN TLV/TWA 50 ppm
THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE				
INGREDIENTS:				
<b>COMPONENT</b>	<b>CAS NO</b>	<b>MAXIMUM%</b>		
TRIMETHLBENZENE	95-63-6		20%	
CUMENE	98-82-8		1.0%	
XYLENE	1330-20-7		1.75%	

**SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS**

**BOILING POINT:** 313-355 ° F  
**MELTING POINT:** N/A  
**VAPOR PRESSURE:** 2.70 mm/Hg @ 20F  
**EVAPORATION RATE (BUOH=1):** 0.1  
**APPEARANCE AND ODOR:** VERY THICK PAINT, VARIOUS COLORS  
 SWEET ODOR.  
**SOLUBILITY IN H2O % BY WT:** SOLUBLE  
**SPECIFIC GRAVITY (H2O=1):** 1.24  
**VAPOR DENSITY (AIR=1):** APPROX. 5  
**PH (AS IS):** 7.5  
**PH (1% SOLN):** NA

**SECTION IV FIRE AND EXPLOSION DATA**

**FLASH POINT: (TEST METHOD):** 106 ° F TCC  
**AUTOIGNITION TEMPERATURE:** 473  
**EXTINGUISHING MEDIA:** EXCLUDE AIR, USE FOAM CO2, STEAM, WATER,  
 FOG, DRY CHEMICALS.  
**SPECIAL FIRE FIGHTING PROCEDURES:** THE USE OF SELF CONTAINED  
 BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS.  
 SEE ALSO SECTION IX.  
**UNUSUAL FIRE AND EXPLOSION HAZARD:** NO UNUSUAL HAZARDS - KEEP  
 WORK AREAS FREE OF HOT METAL AND OTHER SOURCES OF IGNITION.  
**GENERAL HAZARD:** COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE  
 MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT.STATIC  
 DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN  
 CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY"  
 CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND  
 CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE,  
 SOLDER DRILL GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME,  
 SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION:  
 THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS  
 SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY  
 RETURNED TO A DRUM RECONDITIONER ,OR PROPERLY DISPOSED OF.  
**ELECTROSTATIC ACCUMULATION HAZARD: USE PROPER GROUNDING**

-----  
**SECTION V REACTIVITY DATA**  
-----

**CONDITIONS CONTRIBUTING TO INSTABILITY:** PRODUCT IS STABLE  
**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES AND SELECTED AMINES. HAZARDOUS DECOMPOSITION: THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND UNIDENTIFIED ORGANICS.  
**CONDITIONS CONTRIBUTING TO HAZARD POLYMERIZATION:** N/A WILL NOT OCCUR.

-----  
**SECTION VI HEALTH HAZARD INFORMATION**  
-----

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION**

**ROUTES OF EXPOSURE:** THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHT HEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. MINERAL SPIRITS COMPONENTS.

**SKIN CONTACT:** THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.

**SKIN ABSORPTION** SEE ABOVE

**EYE CONTACT:** THIS PRODUCT MAY BE AN EYE IRRITANT. MINERAL SPIRITS COMPONENT.

**EFFECTS OF OVEREXPOSURE TLV - 100 PPM**

**ACUTE OVEREXPOSURE:** ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

**EMERGENCY AND FIRST AID PROCEDURES:**

**EYES:** FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES CONSULT A PHYSICIAN.

**SKIN:** IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

**INHALATION:** MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING, SEEK PROMPT MEDICAL ATTENTION.

-----  
**SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE**  
-----

**AQUATIC TOXICITY (E.G. 96 HR. TLM):**

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, STATE, AND LOCAL REGULATIONS.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** IF POSSIBLE PUMP TO CONTROLLED CONTAINMENT AREA. ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP IS COMPLETE. STOP SPILL AT SOURCE. DIKE SPILL AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINERS.

-----  
**SECTION VIII CONTROL MEASURES**  
-----

**VENTILATION REQUIREMENTS:**

LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY(SPECIFY IN DETAIL):** CHEMICAL CARTRIDGE RESPIRATOR; HALF MASK ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

**EYES:** CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION, OR INJURY.

**GLOVES:** IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

**OTHER CLOTHING AND EQUIPMENT:** TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS ARE RECOMMENDED.

-----  
**SECTION IX SPECIAL PRECAUTIONS**  
-----

**PRECAUTIONARY STATEMENTS:**

PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE RE-USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**OTHER HANDLING AND STORAGE REQUIREMENTS:**

STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

**HMIS HAZARD RATINGS:**

	NPCA-HMIS	NFPA 704	KEY
HEALTH	3		3
			4=SEVERE
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT

0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL IT'S INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

**PREPARED BY**

DARRYL MANUE.L/PRESIDENT

**COMPANY:**

VEXCON CHEMICALS

**ADDRESS:**

7240 STATE RD. , PHILA., PA 19135

**THE INFORMATION PROVIDED IN THIS MATERIAL**

**SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETION OF THE INFORMATION CONTAINED HEREIN**

