

HAZARD RATING
 4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	1
FLAMMABILITY	2
REACTIVITY	2

MATERIAL SAFETY DATA SHEET
 VEXCON NO. CP102B
POWERCOAT® EPOXY FLEXIBLE JOINT SEALANT PART B

GENERAL INFORMATION

PRODUCT IDENTIFICATION:
POWERCOAT® EPOXY FLEXIBLE JOINT SEALANT PART B

VOC CONTENT:

PART A ONLY: <250 g/L OR <2.09 #/GAL.

PART B ONLY: <250 g/L OR <2.09 #/GAL.

AS APPLIED: <250 g/L OR <2.09 #/GAL.

CATEGORY: INDUSTRIAL MAINTENANCE COATING
 (OTC LIMIT 340 g/L; CARB LIMIT 250 g/L)

COMMON NAME: EPOXY SEALANT

DOT SHIPPING NAME:

UN ID NUMBER / SHIPPING NAME / HAZARD CLASS / PKG GROUP
 IN CONTAINERS LESS THAN 119 GALS:

POWERCOAT EPOXY FLEXIBLE JOINT SEALANT PART B (NON-REGULATED)

IN CONTAINERS GREATER THAN 119 GALS:

UN 1866, RESIN SOLUTION (AROMATIC 100 NAPHTHA SOLVENT),
 FLAMMABLE, 3, PG III

FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:

UN 1866, RESIN SOLUTION (AROMATIC 100 NAPHTHA SOLVENT),
 FLAMMABLE 3, PG III, LIMITED QUANTITY

LTD QTY Limits:

Passenger Air Limit 60L (15.8gal); Cargo Air Limit 220L (58.1gal)

ORM-D: MAX. 30 Kg gross wt

HEALTH AND SAFETY: COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL: USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN CONFINED AREA.

SECTION I

MANUFACTURER: VEXCON CHEMICALS, INC.
ADDRESS: 7240 STATE RD., PHILA., PA 19135 USA
EMERGENCY NO: 1-800-858-2828 (PolySat)
TELEPHONE NO: 1-215-332-7709 (Vexcon)
CHEMTREC NO: 1-800-424-9300 (CHEMTREC)
PREPARED: MAY 2000
UPDATED: JULY 2011
PREPARED BY: DARRYL F. MANUEL, PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
BISPHENOL A / EPICHLOROHYDR IN EPOXY RESIN	25068-38-6	75-85%	NONE ESTABLISHED	3082
SOLVENT NAPHTHA (Petroleum), LIGHT AROMATIC	64742-95-6	5-15%	TLV 50 PPM OSHA HAZARD: COMBUSTIBLE	1268
ETHYLENE GLYCOL MONOPROPYL ETHER	002807-30-9	1-5%	OSHA HAZARD: COMBUSTIBLE TLV 100 ppm	1993
PERFORMANCE ADDITIVES	N/A	BAL	N/A	N/A
THE AROMATIC SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:				
COMPONENT	CAS NO.	MAX%	HAZARD DATA	UN#
1,2,4 TRIMETHYL BENZENE	95-63-6	2.0% Max	DOT LABEL: FLAMMABLE LIQUID OSHA PEL not regulated	1993

CUMENE	98-82-8	1.5% Max	ACGIH TLV 25 ppm (TWA) NIOSH REL: 25 ppm (TWA) OSHA PEL: 50 ppm (TWA) ACGIH TLV 50 ppm (TWA)	1918
XYLENE	1330-20-7	2.5% Max	DOT LABEL: FLAMMABLE LIQUID OSHA PEL: 100 ppm (TWA) ACGIH TLV 100 ppm (TWA)	1307

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: (760mmHg) RANGE 161-171C / 322-340 F (AR100)	MELTING/FREEZING POINT: -14 C / 7 F (AR100)
VAPOR PRESSURE: 1.97 mmHg@68°F/20°C (AR100)	VAPOR DENSITY (AIR=1): 4.2 (AR100)
SOLUBILITY IN H2O % BY WT: INSOLUBLE	% VOLATILES BY VOL: 10-20%
EVAPORATION RATE (BuAc=1): SLOW 0.27 (AR100)	SPECIFIC GRAVITY (H2O=1) 1.09
pH (AS IS): N/A	pH (1% SOLN): N/A
APPEARANCE AND ODOR:	CLEAR TO AMBER THICK LIQUID WITH PAINT SOLVENT ODOR

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: (TEST METHOD)	>42°C / 108°F (TCC) (AR100)
AUTOIGNITION TEMP:	479°C / 894°F (AR100)
FLAMMABLE LIMITS IN AIR, % BY VOL:	LOWER: 0.9% UPPER: 6.2% (AR100)
EXTINGUISHING MEDIA:	EXCLUDE AIR. FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER.
GENERAL HAZARD:	COMBUSTIBLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
ELECTRO-STATIC ACCUMULATION HAZARD:	USE PROPER GROUNDING
UNUSUAL FIRE AND EXPLOSION HAZARD:	IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.
SPECIAL FIRE FIGHTING PROCEDURES	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP. USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY:	THIS PRODUCT IS STABLE.
INCOMPATIBILITY:	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS:	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:	N/A WILL NOT OCCUR

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

ROUTES OF EXPOSURE:

INHALATION:	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHTHEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. AROMATIC 100 SOLVENT COMPONENT.
SKIN CONTACT:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 SOLVENT COMPONENT.
SKIN ABSORPTION:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 SOLVENT COMPONENT.
EYE CONTACT:	THIS PRODUCT MAY BE AN EYE IRRITANT. AROMATIC 100 SOLVENT COMPONENT.
INGESTION / INHALATION	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
EFFECTS OF OVEREXPOSURE:	TLV 100 ppm AROMATIC 100 SOLVENT COMPONENT. ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
ACUTE OVEREXPOSURE:	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAIT THE SKIN POSSIBLY CAUSING DERMATITIS.

EMERGENCY AND FIRST AID PROCEDURES:

EYES:	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
SKIN:	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
INHALATION:	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
INGESTION:	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL

AQUATIC TOXICITY (E.G. 96 HR. TLM):	DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:	ELIMINATE SOURCES OF IGNITION (FLARES, FLAMES, PILOT LIGHTS, ELECTRICAL SPARKS). PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. DIKE SPILL AREA WITH SAND OR EARTH TO CONTAIN SPILLED LIQUID AND PREVENT SPREADING. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR WITH ANOTHER SUITABLE ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.
WASTE DISPOSAL METHOD:	IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT, TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS:	LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.
RESPIRATORY (SPECIFY IN DETAIL):	THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA

APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.
EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.
GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.
OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS:	PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.
FIRE FIGHTING:	WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.
OTHER HANDLING AND STORAGE REQUIREMENTS:	STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMIS HAZARD RATINGS:

THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			KEY
POWERCOAT EPOXY FLEXIBLE JOINT SEALANT PART B	NPCA-HMIS	NFPA 704	4 -- SEVERE
HEALTH	1	1	2 -- MODERATE
FLAMMABILITY	2	2	1 -- SLIGHT
REACTIVITY	2	2	0 -- MINIMAL

SECTION X REGULATORY INFORMATION

TSCA:	THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6 (aromatic 100).
CERCLA:	IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675. NO REPORTABLE SPILL QUANTITY (RQ) HAS BEEN ESTABLISHED FOR THIS PRODUCT (AROMATIC SOLVENT NAPHTHA).
SARA TITLE III:	UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: IMMEDIATE, DELAYED, HEALTH, FIRE
ADDITIONAL REGULATORY CONCERNS:	(FEDERAL, FDA, USDA, CPSC, STATE, OTHER) FEDERAL / FDA / USDA:
MARINE POLLUTANT:	THIS PRODUCT CONTAINS A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B): (EPICHLOROHYDRIN, REACTED W/ BIS-A)
	THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A).
CERCLA / RQ:	NONE ESTABLISHED
TSCA:	IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY:	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	