

HAZARD RATING
 4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	2
FLAMMABILITY	3
REACTIVITY	1

MATERIAL SAFETY DATA SHEET
 VEXCON NO. CP107A
POWERCOAT UV+ PART A CLEAR

GENERAL INFORMATION

PRODUCT IDENTIFICATION:
POWERCOAT UV+ PART A CLEAR
VOC CONTENT: AS APPLIED <340 GRAMS/LITER OR <2.84 #/GAL.
 Part A Clear only: 351 g/L or 2.92#/gal / Part B only: .200 g/L or 1.66#/gal
CATEGORY: INDUSTRIAL MAINTENANCE COATING (OTC 340g/L)
COMMON NAME: URETHANE COATING
DOT SHIPPING NAME:
 UN ID NUMBER / SHIPPING NAME / HAZARD CLASS / PKG GROUP
 IN CONTAINERS LESS THAN 119 GALS:
**UN 1866, RESIN SOLUTION (TERTIARY BUTYL ACETATE),
 FLAMMABLE, 3, PG II**
 IN CONTAINERS GREATER THAN 119 GALS:
**UN 1866, RESIN SOLUTION, FLAMMABLE, 3, PG II, RQ
 (TERTIARY BUTYL ACETATE)**
FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:
 UN 1866, RESIN SOLUTION (TERTIARY BUTYL ACETATE),
 FLAMMABLE, 3, PG II, LIMITED QUANTITY
Ltd Qty LIMITS:
 Butyl Acetate: Passenger Air Limit 60L (15.8gal); Cargo Air Limit 220L
 (58.1gal)
 ORM-D: Max. 30 Kg gross wt
HEALTH AND SAFETY: FLAMMABLE LIQUID: USE ONLY WITH ADEQUATE
 VENTILATION: THIS IS A SOLVENT BASED PRODUCT. IF SWALLOWED, DO NOT
 INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER
 PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT:
 ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS
 WHICH CAN BE FATAL: USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT
 IN CONFINED AREA.

SECTION I

MANUFACTURER: VEXCON CHEMICALS, INC.
ADDRESS: 7240 STATE RD., PHILA., PA 19135 USA
EMERGENCY NO: 1-800-858-2828 (PolySat)
TELEPHONE NO: 1-215-332-7709 (Vexcon)
CHEMTREC NO: 1-800-424-9300 (CCN#23822)
PREPARED: DECEMBER 2004
UPDATED: JULY 2011
PREPARED BY: DARRYL F. MANUEL, PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
STYRENE ACRYLATE POLYMER	25036-16-2	20-40%	ND	NONE
TERTIARY BUTYL ACETATE	540-88-5	35-50%	OSHA HAZARD: FLAMMABLE LIQUID OSHA PEL: 200 ppm ACGIH TLV: 200 ppm	1123
ETHYLENE GLYCOL MONOPROPYL ETHER	2807-30-9	1-5%	OSHA HAZARD: COMBUSTIBLE LIQUID Dow IHG 20 ppm TWA ILO 20 ppm; 86 mg/m3	1993
2,6 DIMETHYL-4-HEPTANONE / DIISOBUTYL KETONE	108-83-8	LESS THAN 1%	OSHA HAZARD: FLAMMABLE LIQUID OSHA PEL: 50 ppm ACGIH TLV: 25 ppm	1157
PERFORMANCE ADDITIVES AND FILLERS	N/A	LESS THAN 5%	N/D	NONE
SOLVENT NAPHTHA (Petroleum), LIGHT AROMATIC	64742-95-6	1-5%	TLV 50ppm OSHA HAZARD: COMBUSTIBLE LIQUID	1268
THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:				
COMPONENT	CAS NO.	MAX %	HAZARD DATA	UN#

TRIMETHYL BENZENE	95-63-6	2.5%	OSHA PEL: NE ACGIH TLV: 25ppm	2325
CUMENE	98-82-8	1.1% Max	OSHA PEL: 50 ppm (TWA) ACGIH TLV 50 ppm (TWA)	1918
XYLENE	1330-20-7	2.2% Max	DOT LABEL: FLAMMABLE LIQUID OSHA PEL: 100 ppm (TWA) ACGIH TLV 100 ppm (TWA)	1307

SECTION III PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: (760mmHg) 98 C / 208 F (TBAC)	MELTING/FREEZING POINT: -62 C / 79 F (TBAC)
VAPOR PRESSURE: 41.5 mmHg@68°F/25°C (TBAC)	VAPOR DENSITY (AIR=1): 4.0 (TBAC)
SOLUBILITY IN H2O % BY WT: MISCIBLE	% VOLATILES BY VOL: 65-75%
EVAPORATION RATE (BuAc=1): 2.8 MEDIUM (TBAC)	SPECIFIC GRAVITY (H2O=1) 0.92
pH (AS IS): N/A	pH (1% SOLN): N/A
APPEARANCE AND ODOR: CLEAR LIQUID WITH PAINT SOLVENT ODOR	

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: (TEST METHOD)	4°C / 39°F (TCC) (TBAC)
AUTOIGNITION TEMP:	517°C / 964°F (TBAC)
FLAMMABLE LIMITS IN AIR, % BY VOL:	LOWER: 1.2% UPPER: 6.9% (TBAC)
EXTINGUISHING MEDIA:	EXCLUDE AIR. FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER.
GENERAL HAZARD:	FLAMMABLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
ELECTRO-STATIC ACCUMULATION HAZARD:	USE PROPER GROUNDING
UNUSUAL FIRE AND EXPLOSION HAZARD:	THIS PRODUCT IS FLAMMABLE AND EXPLOSIVE UNDER NORMAL CONDITIONS IN THE PRESENCE OF FLAME OR SPARK SOURCE. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.
SPECIAL FIRE FIGHTING PROCEDURES	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY:	THIS PRODUCT IS STABLE.
--	-------------------------

INCOMPATIBILITY:	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS:	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:	N/A WILL NOT OCCUR

IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA. OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION

BASIS FOR CLASSIFICATION SOURCE

ROUTES OF EXPOSURE:

INHALATION:	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHTHEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. TERTIARY BUTYL ACETATE AND AROMATIC 100 SOLVENT COMPONENTS.
SKIN CONTACT:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. TERTIARY BUTYL ACETATE AND AROMATIC 100 SOLVENT COMPONENTS.
SKIN ABSORPTION:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. TERTIARY BUTYL ACETATE AND AROMATIC 100 SOLVENT COMPONENTS.
EYE CONTACT:	THIS PRODUCT MAY BE AN EYE IRRITANT. TERTIARY BUTYL ACETATE AND AROMATIC 100 SOLVENT COMPONENTS.
INGESTION / INHALATION	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
EFFECTS OF OVEREXPOSURE:	TLV 50 ppm AR-100 ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
ACUTE OVEREXPOSURE:	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.

EMERGENCY AND FIRST AID PROCEDURES:

EYES:	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
SKIN:	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK IMMEDIATE MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
INHALATION:	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
INGESTION:	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL

AQUATIC TOXICITY (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION (FLARES, FLAMES, PILOT LIGHTS, ELECTRICAL SPARKS). PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. DIKE SPILL AREA WITH SAND OR EARTH TO CONTAIN SPILLED LIQUID AND PREVENT SPREADING. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR WITH ANOTHER SUITABLE ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.
WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT, TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.
RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.
EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.
GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.
FIRE FIGHTING: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.
OTHER HANDLING AND STORAGE REQUIREMENTS: STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMS HAZARD RATINGS:			KEY 4 -- SEVERE
THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			
PowerCoat UV+ Part A Clear	NPCA-HMIS	NFPA 704	3 -- SERIOUS
HEALTH	2	2	2 -- MODERATE
FLAMMABILITY	3	3	1 -- SLIGHT
REACTIVITY	1	1	0 -- MINIMAL

SECTION X REGULATORY INFORMATION

TSCA: THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 540-88-5 (tertiary butyl acetate).
CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675. THE REPORTABLE SPILL QUANTITY (RQ) OF THIS PRODUCT IS 5,000 POUNDS / 2267 KILOGRAMS (TERTIARY BUTYL ACETATE).
SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: DELAYED HEALTH, FIRE
ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER) FEDERAL / FDA / USDA:
MARINE POLLUTANTS: THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B).
CERCLA / RQ: 5000 POUNDS / 2267 KILOGRAMS THIS PRODUCT CONTAINS A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A): BUTYL ACETATE.
TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY:	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

