

**HAZARD RATING**  
4=EXTREME  
3=HIGH  
2=MODERATE  
1=SLIGHT  
0=INSIGNIFICANT

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>REACTIVITY</b>	<b>0</b>

**MATERIAL SAFETY DATA SHEET  
VEXCON NO VEXCON NO. CP132 PART B**

**GENERAL INFORMATION**

**PRODUCT IDENTIFICATION:**

MOISTUREBLOC<sup>®</sup> FLEXIBLE JOINT SEALANT PART B

**VOC CONTENT:** 237 GRAMS/LITER 1.98 OR #/GAL.

**CATEGORY:** INDUSTRIAL MAINTENANCE COATING

**COMMON NAME:** EPOXY SEALANT

**DOT SHIPPING NAME:** IN CONTAINERS LESS THAN 119 GALS:  
MOISTUREBLOC<sup>®</sup> FLEXIBLE JOINT SEALANT PART B (NON-REGULATED)  
IN CONTAINERS GREATER THAN 119 GALS:  
RQ, COMBUSTIBLE LIQUID, N.O.S. (AROMATIC SOLVENT), 3, NA 1993, III

**FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:** RQ (AROMATIC SOLVENT RESIN SOLUTION, FLAMMABLE, 3, UN1866, III )

**HEALTH AND SAFETY:** COMBUSTIBLE LIQUID, IF SWALLOWED, DO NOT INDUCE VOMITING; USE ONLY WITH ADEQUATE VENTILATION; USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT.

**SECTION I**

**MANUFACTURER:** VEXCON CHEMICALS, INC.  
7240 STATE RD., PHILA., PA 19135  
**ADDRESS:** USA  
**EMERGENCY NO:** 1-800-858-2828  
**TELEPHONE NO:** 1-215-332-7709  
**CHEMTREC NO:** 1-800-424-9300  
**PREPARED:** MAY 2000  
**UPDATED:** MARCH 2010  
**PREPARED BY:** DARRYL F. MANUEL, PRESIDENT

**SECTION II HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
BISPHENOL A / EPICHLOROHYDRIN EPOXY RESIN	25068-38-6	88%	ND	
AR 100 SOLVENT	64742-95-6	12%	TLV 50 PPM OSHA HAZARD: COMBUSTIBLE	1268
<b>WHICH CONTAINS</b>				
HYDROCARBONS			NOT ESTABLISHED	
1,2,4 TRIMETHYLBENZENE	95-63-6		OSHA PEL & ACGIH TLV/TWA 25 ppm	
XYLENE	1330-20-7		OSHA PEL & ACGIH TLV/TWA 100 ppm	
CUMENE	98-82-8		OSHA PEL & ACGIH TLV/TWA 50 ppm	
<b>THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:</b>				
<b>COMPONENT</b>	<b>CAS NO.</b>	<b>MAX</b>		
TRIMETHYLBENZENE	95-63-6	2%		
CUMENE	98-82-8	1.0%		
XYLENE	1330-20-7	1.75%		

**SECTION III PHYSICAL / CHEMICAL CHARACTERISTICS**

**BOILING POINT:** 313-355°F/156-179°C  
**MELTING POINT:** N/A  
**VAPOR PRESSURE:** 2.70mm/Hg@20F  
**EVAPORATION RATE (BuOH=1):** ND  
**APPEARANCE AND ODOR:**

**SOLUBILITY IN H2O % BY WT:** ND  
**SPECIFIC GRAVITY (H2O=1):** 1.1  
**VAPOR DENSITY (AIR=1):** 4.3  
**% VOLATILES BY VOL:** 13%  
WATER WHITE LIQUID W AROMATIC ODOR

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT (TEST METHOD):** 111°F / 43°C (TCC)

**AUTOIGNITION TEMP:** 869°F / 465°C

**FLAMMABLE LIMITS IN AIR, % BY VOL:** LOWER: 1.0 UPPER: 7.0

**UNUSUAL FIRE AND EXPLOSION HAZARD:** NO UNUSUAL HAZARDS - KEEP WORK AREAS FREE OF HOT METAL

**ELECTROSTATIC ACCUMULATION HAZARD - USE PROPER GROUNDING**

**GENERAL HAZARD:** COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.

**FIRE FIGHTING:** USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. USE FOAM, DRY CHEMICAL, OR WATER SPRAY TO EXTINGUISH FIRE. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER. THE USE OF SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS. SEE ALSO SECTION IX.

**SECTION V REACTIVITY DATA**

**CONDITIONS CONTRIBUTING TO INSTABILITY:** PRODUCT IS STABLE.  
**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES. HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION IN THE PRESENCE OF AIR YIELDS CARBON MONOXIDE AND/OR CARBON DIOXIDE.  
**CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR.

**SECTION VI HEALTH HAZARD INFORMATION**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE**

**ROUTES OF EXPOSURE/INHALATION:** THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION.

AR 100 COMPONENT

**SKIN CONTACT:** THIS PRODUCT MAY RESULT IN SKIN IRRITATION UPON PROLONGED/REPEATED CONTACT.

AR 100 COMPONENT

**SKIN ABSORPTION:** SEE ABOVE

**EYE CONTACT:** THIS PRODUCT MAY BE AN EYE IRRITANT.

AR 100 COMPONENT

**INGESTION:** SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

## **EFFECTS OF OVEREXPOSURE TLV-50 ppm**

**ACUTE OVEREXPOSURE:** ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

## **EMERGENCY AND FIRST AID PROCEDURES:**

**EYES:** FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.

**SKIN:** WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.

**INHALATION:** MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

## **SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL**

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS.

### **STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

**LAND SPILL:** ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS IMPLEMENT CLEAN UP PROCEDURES: FOR LARGE SPILL IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

**WATER SPILL:** REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

## **SECTION VIII CONTROL MEASURES**

**VENTILATION REQUIREMENTS:** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF GENERAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIRPACK.

**EYE:** CHEMICAL GOGGLES AND/OR FACE SHIELDS ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

**GLOVES:** THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS.

**OTHER CLOTHING AND EQUIPMENT:** IMPERMEABLE APRONS AND HELMETS (HEAD COVER) ARE ADVISED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

## **SECTION IX SPECIAL PRECAUTIONS**

### **PRECAUTIONARY STATEMENTS:**

**FIRE FIGHTING:** WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR.

### **HMIS HAZARD RATINGS:**

THIS INFORMATION IS FOR PEOPLE TRAINED IN:  
NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)  
NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704)  
IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

MOISTUREBLOC® FLEXIBLE JOINT SEALANT PART B	NPCA- HMIS	NFPA 704	KEY
HEALTH	2	2	4=SEVERE
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT
			0=MINIMAL

## **SECTION X REGULATORY INFORMATION**

**TSCA:** THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6.

**CERCLA:** IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 800-424-8802. THIS MATERIAL IS COVERED BY CERCLA'S PETROLEUM EXCLUSION, THEREFORE, RELEASES TO AIR, LAND AND WATER ARE NOT REPORTABLE UNDER EPA-CERCLA (SUPERFUND).

**THIS PRODUCT CONTAINS:** XYLENE, CUMENE, TRIMETHYLBENZENE

**SARA TITLE III:** UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES.

**RCRA (40 CFR 261.21) IF THIS PRODUCT BECOMES A WATER MATERIAL, IT WOULD BE AN IGNITABLE HAZARDOUS WASTE. HAZARDOUS WASTE NUMBER D001. REFER TO LATEST EPA OR STATE REGULATIONS REGARDING PROPER DISPOSAL.**

### **DELAYED HEALTH, FIRE.**

FEDERAL:

FDA:

USDA:

**TSCA:** IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? **YES**

**PREPARED BY:** DARRYL MANUEL / PRESIDENT

**COMPANY:** VEXCON CHEMICALS, INC.

**ADDRESS:** 7240 STATE RD., PHILA., PA 19135 USA

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN.