



Protect flooring installations from the ground up.

7240 State Road, Philadelphia, PA 19135
215-332-7709 or 888-839-2661
Fax: 215-332-9997

vexcon.com

MOISTUREBLOC® STRIPPER

HEAVY BODIED SOY BASED STRIPPER

PROFESSIONAL GRADE • ECO-FRIENDLY

DESCRIPTION

MOISTUREBLOC STRIPPER is an eco-friendly heavy bodied stripper designed for the cleaning and removal of coatings and other residues from concrete surfaces.

MoistureBloc Stripper will effectively and safely remove paints, varnishes, urethanes, epoxies, sealers, acrylics, floor waxes and curing compounds from concrete floors receiving MoistureBloc products.

MoistureBloc Stripper will penetrate and remove multiple layers of coatings using less material than traditional stripping products in one application saving time and cost.

MoistureBloc Stripper is derived from soybean oil which is an environmentally friendly bio based agricultural material making it user safe, low odor and easily cleaned up with water.

BENEFITS

- Environmentally friendly
- Made from over 95% renewable resources
- Low odor
- Solvent free
- Removes multiple coating layers
- Professional strength
- Safe to use
- No petroleum solvents

MEETING YOUR INSTALLATION NEEDS

- MoistureBloc products are specially formulated to work together to meet the installation needs of almost any flooring project.

SPECIAL NOTES

- To remove adhesives, use **MoistureBloc Adhesive Remover**
- Do not apply to plastic, PVC or rubber
- Protect all surrounding plant and vegetation with a plastic drop cloth.
- Surface area should be tested to prevent damage to substrate.
- If applying out doors or interior hot or dry conditions cover the area with light plastic drop cloth.
- Do not allow the product to dry on the surface. Keep wet by applying additional material.
- Do not thin MoistureBloc Stripper. It is supplied at the proper consistency for most effective action.
- If using a brush to apply the product do not apply like a paint.
- Shelf life: If properly stored in its original sealed container, three years from date of manufacture. May require mixing. Rotate your stock.
- Proper application of Vexcon material is the responsibility of the installer or user. Telephone consultation and/or field visits by Vexcon personnel are for the sole purpose of making technical recommendations only, and not for providing quality control or supervision on location.

APPLICATION

- Mix well to a uniform consistency prior to application.
- Apply up to 200 sq. ft. (18.6m²) per gallon, depending on thickness and type of coating to be removed, to a thick uniform layer with a brush, squeegee or airless sprayer.
- Allow the stripper time to soften the coating. The rolled product will remain wet for several hours.
- During the stripping process periodically check the stripping action. If the coating is soft enough that it can be removed with a scraper then proceed to remove the entire coating.
- Remove the coating with a floor machine equipped with nylon bristle brush, steel wool, stone media or by scraping.
- Reapply if necessary to remove any remaining material.
- Thoroughly rinse the area with water using a scrub brush mop or power washer.
- After removal of the coating and rinsing, clean the surface with **MoistureBloc Floor Cleaner**.

VITAL STATISTICS

- VOC: N/A
- pH: 8.5
- Flash Point: 235° F/112° C
- Boiling Point: >400° F/204° C
- Autoignition Temp: ND
- Extinguishing Media: Foams, Dry Chemical, CO₂, Water fog or spray.

PACKAGING

MoistureBloc Stripper is available in 55-gallon drums and 5-gallon pails. Contact Vexcon to discuss your customized packaging requirements.

HEALTH AND SAFETY

- Caution, slippery when applied. Use care when walking.
- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.

The stripper solution and/or materials may be classified as a hazardous material for purposes of disposal. This material should be kept in a separate container and local, State and federal rules for disposal must be followed. Vexcon MSDS #CP158 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product, it is advisable to obtain a copy of the MSDS from your distributor or by contacting Vexcon Chemicals.

CONTACT US@

Additional product information, technical assistance and customer services are available by contacting Vexcon Chemicals directly, or our distributors.

- vexcon.com
- techservice@vexcon.com
- customerservice@vexcon.com
- sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES.

No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.