



CERTI-VEX[®] LINSEED ANTISPALL

Linseed Antispall Compound

VOC Content: 392 gr./liter or 3.27#/gal – Concrete Protective Coating

DESCRIPTION

CERTI-VEX LINSEED ANTISPALL is an advanced formulation of 50% boiled linseed and solvents manufactured with special additives to maximize the antispalling protection of concrete. When properly applied to cured concrete, Certi-Vex Linseed Antispall acts as a barrier protecting the concrete from potential damage from freeze/thaw cycles and corrosive salts.

BENEFITS

- Life expectancy of concrete greatly extended
- Maximum penetration when properly applied
- Protection against freeze/thaw cycles and corrosive salts
- Minimizes maintenance and repair costs
- Meets all standard state specification and in most areas is available pre-approved for use
- Can apply to 20⁰F – Request Cold Weather Application Guide

APPLICATION

Apply Certi-Vex Linseed Antispall to cured concrete that is at least 28 days old. Do not add thinner as product is supplied at the proper consistency for spraying. Dilution will reduce efficiency.

Thoroughly mix by mechanical methods before use to ensure best results and ease of application. Apply by brush, roller or sprayer, however, application by sprayer is preferred. Apply at 400-500 sq.ft./gal. (10-12.5 m²/L). Clean up equipment with **Certi-Vex[®] Equipment Cleaner**.

Coat Uniformly - Leave no Gaps

SPECIFICATIONS/COMPLIANCE

- Meets EPA & AIM VOC regulations

The boiled linseed portion of Certi-Vex Linseed Antispall complies to:

- AASHTO M-233 and ASTM D260 Type1.

The solvent portion of Certi-Vex Linseed Antispall complies with:

- ASTM D235 and AASHTO M126, M128 and M233
- Meets the requirements of federal specifications FSS TT-L-190C and FSS TT-L-291C
- USDA approved

PACKAGING

Certi-Vex Linseed Antispall is available in 55-gallon drums and 5-gallon pails. Also available in totes and bulk shipments. Contact Vexcon to discuss your customized packaging requirements.

VITAL STATISTICS

- Flash Point: 106° F (41° C) TCC Typical
- Boiling Point: 310-405° F (154-207° C)
- Autoignition temp: ND
- Extinguishing media: Foam, dry chemical, CO₂, water fog or spray.

PHYSICAL PROPERTIES

- Color 10-11 Gardner
- Dry Time (200 sq.ft./gal) 3 hours
- Solids 50/50 in mineral spirits by volume.
- Solvents: Mineral Spirits
- Wt/Gal: 7.14

HEALTH AND SAFETY

- Use only with adequate ventilation
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.

Vexcon MSDS #CT107 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product it is advisable to get a copy of the MSDS, #CT107, from your distributor or by contacting Vexcon Chemicals

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or our distributors. Certi-Vex Linseed Antispall is available at stocking distributors nationwide.

- www.vexcon.com
- Technicalservice@vexcon.com
- Customerservice@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

SHELF LIFE

If properly stored in its original sealed container, three years from date of manufacturer. Rotate your stock.