

CERTI-VEX[®] LINSEED ANTISPALL

Linseed Antispall Compound

DESCRIPTION

CERTI-VEX LINSEED ANTISPALL is an advanced formulation of 50% boiled linseed and solvents manufactured with special additives to maximize the antispalling protection of concrete. When properly applied to cured concrete, Certi-Vex Linseed Antispall acts as a barrier protecting the concrete from potential damage from freeze/thaw cycles and corrosive salts.

BENEFITS

- Life expectancy of concrete greatly extended
- Maximum penetration when properly applied
- Protection against freeze/thaw cycles and corrosive salts
- Minimizes maintenance and repair costs
- Meets all standard state specification and in most areas is available pre-approved for use
- Can apply to 20⁰F – Request Cold Weather Application Guide

APPLICATION

Apply Certi-Vex Linseed Antispall to cured concrete that is at least 28 days old. Do not add thinner as product is supplied at the proper consistency for spraying. Dilution will reduce efficiency. Thoroughly mix by mechanical methods before use to ensure best results and ease of application. Apply by brush, roller or sprayer, however, application by sprayer is preferred. Apply at 400-500 sq.ft./gal. (10-12.5 m²/L). Clean up equipment with **Certi-Vex[®] Equipment Cleaner. Coat Uniformly - Leave no Gaps**

SPECIFICATIONS/COMPLIANCE

- VOC <400 grams/ Liter or < 3.33 #/gal
- Meets
 - US EPA AIM - Waterproofing Concrete/Masonry Cleaner
 - OTC-Waterproofing Concrete/Masonry Sealer
 - LADCO-Waterproofing Concrete/Masonry Sealer
 - Canada-Waterproofing Concrete/Masonry Sealer

The boiled linseed portion of Certi-Vex Linseed Antispall complies to:

- AASHTO M-233 and ASTM D260 Type 1.

The solvent portion of Certi-Vex Linseed Antispall complies with:

- ASTM D235 and AASHTO M126, M128 and M233
- Meets the requirements of federal specifications FSS TT-L-190C and FSS TT-L-291C
- USDA approved

PACKAGING

Certi-Vex Linseed Antispall is available in 55-gallon drums and 5-gallon pails. Also available in totes and bulk shipments. Contact Vexcon to discuss your customized packaging requirements.

VITAL STATISTICS

- Flash Point: 106°F (41°C) TCC Typical
- Boiling Point: 310-405°F (154-207°C)
- Autoignition temp: ND
- Extinguishing media: Foam, dry chemical, CO₂, water fog or spray.

PHYSICAL PROPERTIES

- Color 10-11 Gardner
- Dry Time (200 sq.ft./gal) 3 hours
- Solids 50/50 in mineral spirits by volume.
- Solvents Mineral Spirits
- Wt/Gal 7.14

SHELF LIFE

If properly stored in its original sealed container, three years from date of manufacturer. Rotate your stock.

HEALTH AND SAFETY

- Use only with adequate ventilation
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.

Vexcon MSDS CT107 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product it is advisable to get a copy of the MSDS, CT107, from your distributor or by contacting Vexcon Chemicals

CONTACT US @

Additional product information, technical assistance and customer services are available by contacting Vexcon Chemicals directly or our distributors.

- vexcon.com
- techservice@vexcon.com
- customerservice@vexcon.com
- sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES.

No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.