STARSEAL® EF CURE

INSTRUCTIONS FOR USE

APPLICATION

- Apply as soon as possible after concrete receives final finishing, just as the water sheen disappears. If application is delayed, concrete must be kept wet, preferably by water spray mist, until the product is applied.
- Do not add thinner as product is supplied at the proper consistency for spraying. Dilution will reduce curing efficiency.
- Thoroughly mix by air or mechanical methods before use to ensure best results and ease of application.
- Apply by brush, roller or sprayer; however, application by sprayer is preferred.
- Apply at 200 sq.ft./gal. (7.5 m^2/L) or less depending on method of application and specification requirements.
- Curing shall be maintained for a minimum of seven (7) days or until seventy (70) percent of the specified concrete strength has been obtained.

SPECIAL NOTES

- If StarSeal EF Cure is supplied with a red fugitive dye, do not use for interior applications. Dye will disappear after prolonged exposure to sunlight.
- Can apply to 40°F.
- Do not apply on windy days.
- Do not apply when surface temperatures are above 85°F.
- Keep from freezing.
- Mix well before each use.
- Shelf Life: If properly stored in its original sealed container, two years from date of manufacture. Rotate your stock.

TOPCOATS AND ADHESIVES

StarSeal EF Cure is a dissipating curing compound that will slowly flake off after exposure to UV, weathering and/or construction traffic. Topcoats and adhesives are not recommended for use over StarSeal EF Cure unless the entire surface area is free of residue. Residue should be removed by wire brushing or by using **StarSeal EF Stripper**. For alternative methods of removal, contact the manufacturer. StarSeal EF Cure should not be used as a sealer. Use **StarSeal EF** acrylic curing and sealing products for sealing applications.

VITAL STATISTICS

• Flash Point	>200°F (>93°C)
• Boiling Point	208°F (98°C)
• Autoignition Temp	964°F (517°C)
• Extinguishing Media	Foam, Dry chemical, CO_2, Water Fog

HEALTH AND SAFETY

- Use only with adequate ventilation
- Use of gloves, goggles and other protective clothing is advised when using this product
- If swallowed, do not induce vomiting

VEXCON MSDS EFCC200 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using product, it is advisable to obtain a copy of the MSDS EFCC200 from your distributor or by contacting Vexcon.

CONTACT US @

Additional product information, technical assistance and customer services are available by contacting Vexcon Chemicals directly, or our distributors.

- vexcon.com
- sales@vexcon.com
- techservice@vexcon.com
- Voice: 888.839.2661
- customerservice@vexcon.com
- Fax: 215.332.9997

Proper application of Vexcon material is the responsibility of the installer or user. Telephone consultation and/or field visits by Vexcon personnel are for the sole purpose of making technical recommendations only, and not for providing quality control or supervision on location.

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES.

No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.