

## CERTI-VEX<sup>®</sup> CONCRETE STRIPPER VERTICAL

### HEAVY BODIED CONCRETE STRIPPER USED TO REMOVE COATINGS FROM VERTICAL SURFACES

#### DESCRIPTION

**CERTI-VEX CONCRETE STRIPPER VERTICAL** is a scientifically formulated heavy bodied concrete stripper, with a light grease consistency, especially designed for the cleaning and the removal of coatings and other residues from vertical surfaces. After use, Certi-Vex Concrete Stripper Vertical is emulsifiable with water and general cleaners to yield a stripped concrete surface that is clean and ready for subsequent treatments.

#### APPLICATION

- Mix well prior to application to a uniform consistency.
- Apply a thick uniform layer with a brush or airless sprayer.
- Allow the stripper time to soften the coating. The product will remain wet for several hours.
- During the stripping process periodically check the stripping action. If the coating is soft enough that it can be removed with a scraper then proceed to remove the entire coating.
- Remove the cleaner with a hand-held buffer, a grinder equipped with a white 3 M type pad, by scraping or wiping or pressure wash when removing graffiti from uncoated surface.
- Reapply if necessary to remove any remaining material.
- Thoroughly rinse the area with water using a scrub brush or power washer.
- After removal of the coating and rinsing, clean the surface with **Certi-Vex<sup>®</sup> Super Degreaser & Cleaner**.
- Apply a test patch before any protective treatment application.

#### SPECIAL NOTES

- Do not apply to plastic, PVC or rubber.
- Use **Certi-Vex Concrete Stripper** for horizontal applications.
- Protect all surrounding plant and vegetation with a plastic drop cloth.
- Surface area should be tested to prevent damage to substrate.
- If applying outdoors or interior hot or dry conditions cover the area with poly sheet pressed into stripper to keep from drying.
- Do not allow the product to dry on the surface. Keep wet by applying additional material.
- Do not thin Certi-Vex Concrete Stripper Vertical. It is supplied at the proper consistency for most effective action.
- If using a brush to apply the product do not apply like a paint.
- Proper application of Vexcon material is the responsibility of the installer or user. Telephone consultation and/or field visits by Vexcon personnel are for the sole purpose of making technical recommendations only, and not for providing quality control or supervision on location.

#### PROTECT

After use, finish your surface with one of Vexcon's premium vertical coatings. Contact Vexcon for product recommendations.

#### COVERAGE RATE

- Vertical Up to 200 sq. ft. per gallon depending on thickness and type of coating to be removed.

#### PACKAGING

Certi-Vex Concrete Stripper Vertical is available in 55-gallon drums, 5-gallon pails and 1-gallon units. Contact Vexcon directly to discuss your customized packaging requirements.

#### VITAL STATISTICS

- Flash Point 140°F (60°C) TCC
- Boiling Point 310-428°F (154-220°C)
- Autoignition Temp ND
- Extinguishing Media Foams, Dry Chemical, CO<sub>2</sub>, Water fog or spray

#### SHELF LIFE

If properly stored in its original sealed container, three years from date of manufacture. May require mixing. Rotate your stock.

#### HEALTH AND SAFETY

- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Aspiration of materials into the lungs can cause chemical pneumonitis, which can be fatal.
- Use of respirators is advised when using this product in confined areas.

The stripper solution and/or materials may be classified as a hazardous material for purposes of disposal. This material should be kept in a separate container; local, state, and federal rules for disposal must be followed. Contact Vexcon if additional questions and/or information is required. Vexcon MSDS #OP102 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product, it is advisable to get a copy of the MSDS from your distributor or by contacting Vexcon Chemicals.

#### CONTACT US@

Additional product information, technical assistance and customer services are available by contacting Vexcon Chemicals directly, or our distributors.

- [sales@vexcon.com](mailto:sales@vexcon.com)
- [techservice@vexcon.com](mailto:techservice@vexcon.com)
- [customerservice@vexcon.com](mailto:customerservice@vexcon.com)
- Voice: 888.839.2661
- Fax: 215.332.9997

#### WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.