



HAZARD RATING
4=EXTREME
3=HIGH
2=MODERATE
1=SLIGHT
0=INSIGNIFICANT

| | |
|---------------------|----------|
| HEALTH | 2 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |

MATERIAL SAFETY DATA SHEET
VEXCON NO. OP102
CONCRETE STRIPPER VERTICAL

GENERAL INFORMATION

PRODUCT IDENTIFICATION:

CERTI-VEX® CONCRETE STRIPPER VERTICAL

VOC CONTENT: NOT REQUIRED

CATEGORY: CONCRETE CLEANER, NO COATING CATEGORY FOR VOC

COMMON NAME: SOLVENT CONCRETE STRIPPER

DOT SHIPPING NAME:

UN NUMBER / SHIPPING NAME / HAZARD CLASS / PACKING GROUP
IN CONTAINERS LESS THAN 119 GALS BY GROUND SHIPPING:

CERTI-VEX CONCRETE STRIPPER VERTICAL (NON-REGULATED)

IN CONTAINERS GREATER THAN 119 GALS:

UN 1263, PAINT RELATED MATERIAL, 3, III

FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:

UN 1263, PAINT RELATED MATERIAL, 3, III

ORM-D LIMIT: 5 LITRES

HEALTH AND SAFETY: FLAMMABLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPEMENT IS ADVISED WHEN HANDLING THIS PRODUCT. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL: USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN CONFINED AREA.

SECTION I

MANUFACTURER: VEXCON CHEMICALS, INC.
ADDRESS: 7240 STATE RD., PHILA., PA 19135 USA
EMERGENCY NO: 1-800-858-2828 (PolySat)
TELEPHONE NO: 1-215-332-7709 (Vexcon)
CHEMTREC NO: 1-800-424-9300 (CCN# 23822)
PREPARED: FEBRUARY 1999
UPDATED: JUNE 2011
PREPARED BY: DARRYL F. MANUEL, PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

| MATERIAL OR COMPONENTS | CAS NO. | HAZARD DATA | UN# |
|---|-------------|--|------|
| PINE OIL (TERPENE ALCOHOLS) | COMBUSTIBLE | NOT ESTAB. | 1272 |
| ETHYLENE GLYCOL MONOPROPYL ETHER | 2807-30-9 | 100 ppm TLV (Dow IHG 20 ppm TWA, 60 ppm STEL) | 1987 |
| SOLVENT NAPHTHA (Petroleum), LIGHT AROMATIC | 64742-95-6 | TLV 50ppm OSHA HAZARD: COMBUSTIBLE LIQUID | 1268 |
| SILICA, AMORPHOUS, FUMED | 112945-52-5 | OSHA 20 MPPCF 0.8 mg/m3 TWA ACGIH TWA 10 mg/m3 Inhalable Dust | NONE |
| BENTONITE CLAY | 68953-58-2 | AS QUARTZ, PRESENT AT LESS THAN 1% ACGIH 0.1 mg/m3 OSHA PEL (resp) 10 mg/m3 / % SiO2 + 2 OSHA PEL (total dust) 30 mg/m3 / % SiO2 + 2 | NONE |
| ATTAPULGITE CLAY | 12174-11-7 | AS QUARTZ, PRESENT AT LESS THAN 10% ACGIH 0.1 mg/m3 OSHA PEL (resp) 10 mg/m3 / % SiO2 + 2 OSHA PEL (total dust) 30 mg/m3 / % SiO2 + 2 | NONE |
| PERFORMANCE ADDITIVES | N/A | N/A | NONE |

| THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS: | | | |
|--|-----------|---|------|
| COMPONENT | CAS NO. | HAZARD DATA | UN# |
| 1,2,4-TRIMETHYL BENZENE (PSEUDO CUMENE) | 95-63-6 | OSHA PEL: NE ACGIH TLV: 25ppm (TWA) | 1993 |
| XYLENES | 1330-20-7 | OSHA Z1 100ppm (TWA) ACGIH TLV 100ppm (TWA) NIOSH REL 100 ppm (TWA) | 1307 |
| CUMENE | 98-82-8 | OSHA Z1 50ppm (TWA) ACGIH TLV 50ppm (TWA) | 1918 |

SECTION III PHYSICAL / CHEMICAL CHARACTERISTICS

| | |
|--|--|
| BOILING POINT: (760mmHg) 161-171 C / 322-340 F (AR100) | MELTING/FREEZING POINT: -14 C, 7 F (AR100) |
| VAPOR PRESSURE: 1.97 mmHg@68°F/20°C (AR100) | VAPOR DENSITY (AIR=1): 4.2 (AR100) |
| SOLUBILITY IN H2O % BY WT: MISCIBLE | % VOLATILES BY VOL: N/A |
| EVAPORATION RATE (BuAc=1): 0.27 SLOW (AR100) | SPECIFIC GRAVITY (H2O=1) 0.973 |
| pH (AS IS): N/A | pH (1% SOLN): N/A |
| APPEARANCE AND ODOR: | PALE YELLOW LIQUID WITH SWEET PINE ODOR |

SECTION IV FIRE AND EXPLOSION DATA

| | |
|--|---|
| FLASH POINT: (TEST METHOD) | 60°C / 140°F (TCC) |
| AUTOIGNITION TEMP: | 479°C / 894°F (AR100) |
| FLAMMABLE LIMITS IN AIR, % BY VOL: | LOWER: 0.9% UPPER: 6.2% (AR100) |
| EXTINGUISHING MEDIA: | FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER. |
| GENERAL HAZARD: | COMBUSTIBLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF. |
| ELECTRO-STATIC ACCUMULATION HAZARD: | USE PROPER GROUNDING |
| UNUSUAL FIRE AND EXPLOSION HAZARD: | IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION. |
| SPECIAL FIRE FIGHTING PROCEDURES | THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. |

STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT **COOL WITH WATER SPRAY** IN ORDER TO PREVENT PRESSURE BUILD UP.

SECTION VIII CONTROL MEASURES

SECTION V REACTIVITY DATA

| | |
|---|--|
| CONDITIONS CONTRIBUTING TO INSTABILITY: | THIS PRODUCT IS STABLE. |
| INCOMPATIBILITY: | THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES. |
| HAZARDOUS DECOMPOSITION PRODUCTS: | THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS. |
| CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: | N/A WILL NOT OCCUR |

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

ROUTES OF EXPOSURE:

| | |
|---------------------------------|--|
| INHALATION: | THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. AROMATIC 100 SOLVENT COMPONENT. |
| SKIN CONTACT: | THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 SOLVENT COMPONENT. |
| SKIN ABSORPTION: | THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 SOLVENT COMPONENT. |
| EYE CONTACT: | THIS PRODUCT MAY BE AN EYE IRRITANT. AROMATIC 100 SOLVENT COMPONENT. |
| INGESTION / INHALATION | SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION. |
| EFFECTS OF OVEREXPOSURE: | TLV 50-100 ppm ESTIMATED FROM SIMILAR PRODUCTS ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES. |
| ACUTE OVEREXPOSURE: | ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS. |

EMERGENCY AND FIRST AID PROCEDURES:

| | |
|--------------------|---|
| EYES: | FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION. |
| SKIN: | WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS. |
| INHALATION: | MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. |
| INGESTION: | DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION. |

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL

AQUATIC TOXICITY (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

FIRE FIGHTING: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.

OTHER HANDLING AND STORAGE REQUIREMENTS: STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMSI HAZARD RATINGS:

THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

KEY

4 -- SEVERE

| VEXCON CERTI-VEX CONCRETE STRIPPER | NPCA-HMIS | NFPA 704 | |
|------------------------------------|-----------|----------|---------------|
| HEALTH | 2 | 2 | 2 -- MODERATE |
| FLAMMABILITY | 2 | 2 | 1 -- SLIGHT |
| REACTIVITY | 0 | 0 | 0 -- MINIMAL |

SECTION X REGULATORY INFORMATION

TSCA: THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6 (AROMATIC 100).

CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675.

NO REPORTABLE SPILL QUANTITY (RQ) HAS BEEN ESTABLISHED FOR THIS PRODUCT.

SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: DELAYED HEALTH, FIRE

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

FEDERAL:

CERCLA / RQ: **NONE**

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? **YES**

PREPARED BY DARRYL MANUEL / PRESIDENT
 COMPANY: VEXCON CHEMICALS, INC.
 ADDRESS: 7240 STATE RD., PHILA, PA 19135 USA

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.