

HAZARD RATING

4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

MATERIAL SAFETY DATA SHEET
VEXCON NO. OP105



Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA. 19135
 VOICE: 215.332.7709 • FAX: 215.332.9997
 TOLL FREE: 888-VEXCON-1
 WEBSITE ADDRESS: www.vexcon.com

GENERAL INFORMATION

PRODUCT IDENTIFICATION: CERTI-VEX® EQUIPMENT CLEANER
VOC CONTENT: NOT REQUIRED **CATEGORY:** NOT REQUIRED
COMMON NAME: HIGH FLASH AROMATIC SOLVENT
DOT SHIPPING NAME: IN CONTAINERS LESS THAN 119 GALS: AROMATIC SOLVENT (NON-REGULATED)
HEALTH AND SAFETY: OMBUSTIBLE LIQUID: IF SWALLOWED, DO NOT INDUCE VOMITING: USE ONLY WITH ADEQUATE VENTILATION: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT.

SECTION I

MANUFACTURER: VEXCON CHEMICALS
EMERGENCY NO: 1-800-858-2828
CHEMTREC NO: 1-800-424-9300
TELEPHONE NO: 1-215-332-7700
ADDRESS 7240 STATE RD. PHILA., PA. 19135
PREPARED: MAY 1996
UPDATED: SEPTEMBER 13, 1999
PREPARED BY: DARRYL F. MANUEL/PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT	CAS NO.	%	HAZARD LIMIT	UN
AR 100 SOLVENT WHICH CONTAIN HYDROCARBONS 1,2,4 TRIMETHYBENZENE	64742-95-6	100%	TLV 50 PPM OSHA HAZARD COMBUSTIBLE NOT ESTABLISHED OSHA PEL:ACGIN TLV/TWA 25ppm	1255
XYLENE	95-63-6		OSHA PEL:ACGIN TLV/TWA 100ppm	
CUMENE	98-82-8		OSHA PEL:ACGIN TLV/TWA 50ppm	

THE FOLLOWING PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS.

COMPONENT	CAS NO	MAXIMUM %
TRIMETHLBENZENE	95-63-6	40%
CUMENE	98-82-8	2.0%
XYLENE	1330-20-7	3-4%

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 760 mm Hg: 313-355°F **MELTING POINT:** N/A
SPECIFIC GRAVITY (H2O=1): .948 (60/60°F)
VAPOR PRESSURE: 2.70 mm/Hg @20F **VAPOR DENSITY (AIR = 1):** 4.3
SOLUBILITY IN H2O % BY WT: INSOLUBLE
% VOLATILES BY VOL: 52%
EVAPORATION RATE (BUAC=1): .1
 PH (AS IS) N/A PH (1% SOLN.): N/A
APPEARANCE AND ODOR: WATER WHITE LIQUID /AROMATIC ODOR

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): 111° F TCC **AUTOIGNITION TEMP:** 869° F
FLAMMABLE LIMITS IN AIR, % BY VOL: **LOWER:** 1.0 **UPPER:** 7.0
UNUSUAL FIRE AND EXPLOSION HAZARD NO UNUSUAL HAZARDS - KEEP WORK AREAS FREE OF HOT METAL

GENERAL HAZARD: COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT.STATIC DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE, SOLDER DRILL GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER ,OR PROPERLY DISPOSED OF.

ELECTROSTATIC ACCUMULATION HAZARD - USE PROPER GROUNDING

FIRE FIGHTING: USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. USE FOAM, DRY CHEMICAL, OR WATER SPRAY TO EXTINGUISH FIRE. AVOID SPRAYINGWATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER. THE USE OF SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS. SEE ALSO SECTION IX.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: PRODUCT IS STABLE.

INCOMPATIBILITY: THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS STRONG ACIDS OR BASES AND SELECTED AMINES.

HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION IN THE PRESENCE OF AIR YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

ROUTES OR EXPOSURE/INHALATION: THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTHEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. AR 100 COMPONENT

SKIN CONTACT THIS PRODUCT MAY RESULT IN SKIN IRRITATION

UPON PROLONGED/REPEATED CONTACT. AR 100 COMPONENT

SKIN ABSORPTION SEE ABOVE

EYE CONTACT: HIS PRODUCT MAY BE AN EYE IRRITANT.
AR 100 COMPONENT

INGESTION:SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

EFFECTS OF OVEREXPOSURE TLV-50 ppm

ACUTE OVEREXPOSURE:ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

EMERGENCY AND FIRST AID PROCEDURES:

EYES FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.

SKIN: WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.

INHALATION: MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

INGESTION:DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL

WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, STATE, AND LOCAL REGULATIONS.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL, IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS IMPLEMENT CLEANUP PROCEDURES: FOR LARGE SPILL IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE CONTAIN SPILLED LIQUID WITH SAND OR AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND EN-SURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSENTS MAY BE USED IN ON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF GENERAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF A OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIRPACK.

EYE: CHEMICAL GOGGLES AND/OR FACE SHIELDS ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS.

OTHER CLOTHING AND EQUIPMENT: IMPERMEABLE APRONS AND HELMETS (HEAD COVER) ARE ADVISED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

FIRE FIGHTING:WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

OTHER HANDLING AND STORAGE REQUIREMENTS: KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR.

HMIS HAZARD RATINGS:

THIS INFORMATION IS FOR PEOPLE TRAINED IN:
NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA)
HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)
NATIONAL FIRE PROTECTION ASSOCIATION (NEPA 704)
IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

	NPCA-HMIS	NFPA 704	KEY
HEALTH	2	2	4=SEVERE
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	2=MODERATE 1=SLIGHT 0=MINIMAL

SECTION X REGULATORY INFORMATION

TSCA: THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN. VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-96-6.

CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 800-424-8802. THIS MATERIAL IS COVERED BY CERCLA'S PETROLEUM EXCLUSION, THEREFORE, RELEASES TO AIR, LAND AND WATER ARE NOT REPORTABLE UNDER EPA-CERCLA (SUPERFUND).

THIS PRODUCT CONTAINS: XYLENE, CUMENE, TRIMETHYLBENZENE

SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: **RCRA (40 CFR 261.21) IF THIS PRODUCT BECOMES A WASTE MATERIAL, IT WOULD BE AN IGNITABLE HAZARDOUSWASTE. HAZARDOUS WASTE NUMBER D001. REFER TO LATEST EPA OR STATE REGULATIONS REGARDING PROPER DISPOSAL.**

DELAYED HEALTH, FIRE.

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY:

DARRYL MANUEL

TITLE:

PRESIDENT

COMPANY:

VEXCON CHEMICALS

ADDRESS

7240 STATE RD., PHILA., PA. 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN