



CERTI-VEX[®] COATING REPAIR

DESCRIPTION

CERTI-VEX COATING REPAIR will effectively re-cast an existing coating correcting application imperfections, such as bubbles and over applied thick coatings. Once corrected, the coated floor will have a uniform appearance.

BENEFITS

- Slower evaporation rate than Xylene or Toluene
- Enhances uniform film formation
- Can be used on solvent and waterbased coatings
- Slower evaporation rate helps keep film open to minimize air bubble formation
- Reduces cob webbing
- Non-Red Label

APPLICATION

- Apply with an **Evenflow Applicator** or ¼ "nap mohair roller
- Use a roller pan to remove excess Coating Repair material from the roller
- Do not dip and roll or pour and spread
- Apply a thin amount to the affected area in a lapping motion to re-dissolve the surface film of the coating; it will re-dissolve the film, blending air bubbles and film imperfections.
- Heavy applications of sealer may require another treatment
- Leave dry overnight with good ventilation before using floor

SPECIAL NOTES

- May affect some surface areas if splashed.
- If coating needs to be removed use **Certi-Vex[®] Concrete Stripper**

WARNING

When used, the material may be classified a hazardous material for purposes of disposal. This material should be kept in a separate container and local, state, federal rules for disposal must be followed. Contact Vexcon if additional questions and/or information is required and consult the Material Safety Data Sheet.

PACKAGING

Certi-Vex Coating Repair is available in 55-gallon drums, 5-gallon pails and 1-gallon containers. Contact Vexcon to discuss your customized packaging requirements.

VITAL STATISTICS

- Flash Point 111° F (44° C) TCC
- Boiling Point 300-355° F (149-180° C)
- Autoignition Temp >1000° F
- Extinguishing Media Foams, Dry Chemical, CO₂, Water fog.

HEALTH AND SAFETY

- Use only with adequate ventilation, Combustible liquid.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.

Vexcon MSDS is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product obtain a copy of the MSDS from your distributor or by contacting Vexcon Chemicals.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or our distributors.

- www.vexcon.com
- TechnicalService@vexcon.com
- CustomerService@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997