

HAZARD RATING

4=EXTREME
3=HIGH
2=MODERATE
1=SLIGHT
0=INSIGNIFICANT

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

**MATERIAL SAFETY DATA SHEET
VEXCON NO. OP130**



Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA. 19135
VOICE: 215.332.7709 • FAX: 215.332.9997
TOLL FREE: 888-VEXCON-1
WEBSITE ADDRESS: www.vexcon.com

GENERAL INFORMATION

PRODUCT IDENTIFICATION: CERTI-VEX NON-SLIP EPOXY ADDITIVE

COMMON NAME: SILICA SAND

DOT SHIPPING NAME: CERTI-VEX NON SLIP ADDITIVE

HEALTH AND SAFETY: THIS PRODUCT IS A POWDERED SOILD. CONTINUED INFALATION OF DUST OVER A PERIOD OF YEARS WITHOUT PROPER RESPIRATOR AND VENILATION CONTROLS WILL CAUSE SILICOSIS AND LUNG CANCER. USED ONLY WITH SAFETY GLASSES, NEOPRENE GLOVES AND PROTECTIVE CLOTHING RECOMMENDED.

SECTION I

MANUFACTURER: VEXCON CHEMICALS
EMERGENCY NO: 1-800-858-2828
CHEMTREC NO: 1-800-424-9300
TELEPHONE NO: 1-215-332-7709
ADDRESS: 7240 STATE RD.,PHILA.,PA. 19135
PREPARED: SEPTEMBER 2000
PREPARED BY: DARRYL F. MANUEL/PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

<u>MATERIAL OR COMPONENTS</u>	<u>CAS. NO.</u>	<u>%</u>	<u>OSHA PEL:</u>	<u>ACGHI TLV</u>
SILICA SAND*	14808-60-7	100	0.1 mg m3	0.1 mg/m3

*CONTINUED INHALATION OF DUST OVER A PERIOD OF YEARS WITHOUT PROPER RESPIRATOR AND VENTILATION CONTROLS WILL CAUSE SILICOSIS AND LUNG CANCER. CURRENT OSHA STANDARD FOR CRYSTALLINE SILICA (RESPIRABLE DUST) IS 10mg SILICA PER CUBIC METER OF AIR DIVIDED BY THE PERCENT S102 AVENTRAGED OVER AN EIGHT HOUR WORK SHIFT AND FOR TOTAL DUST IS 30mg/m3 DIVIDED BY THE PERCE S102 AVERAGED OVER AN EIGHT HOUR WORK SHIFT.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/A **MELTING PIONT:** N/A
SPECIFIC GRAVITY (H2O=1): 2.65 **VAPOR PRESSURE (AIR=1):**N/A
VAPOR DENSITY (mmhg): N/A
APPEARANCE AND ODOR: GRAY NO ODOR **PH (AS IS)**
EVAPORATION RATE: N/A **FREEZING POINT:** N/A

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: N/A **AUTOIGNITION TEMPERATURE:** N/A
FLAMMABLE LIMITS IN AIR: % BY VOL: N/A
UNUSUAL FIRE AND EXPLOSION HAZARD: N/A NOT COMBUSTIBLE OR EXPLOSIVE

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: WATER
INCOMPATIBILITY: NONE
HAZARDOUS DECOMPOSITION PRODUCT: NONE
CONDITIONS CONTRIBUTING TO HAZARD
POLYMERIZATION: N/A WILL NOT OCCUR.

SECTION IV HEALTH HAZARD INFORMATION

ROUTES OF EXPOSURE:
INHALATION: DUST CAN CAUSE INFLAMMATION OF NOSE TISSUE LINING AND CORNEA. HYPERSENSITIVITY MAY CAUSE ALLERGIC DERMATITIS. CONTINUED INHALATION OF DUST OVER A PERIOD OF YEARS WITHOUT PROPER RESPIRATOR AND VENTILATION CONTROLS WILL CAUSE SILICOSIS AND LUNG CANCER.
SKIN CONTACT: PRODUCT IS ALKALINE AND CAN IRRITATE THE SKIN
SKIN ABSORPTION: SEE ABOVE
EYE CONTACT: THIS PRODUCT MAY BE AN EYE IRRITANT.

INGESTION/IHALATON: CURRENT OSHA STANDARDS FOR CRYSTALLINE SILICA IS 10mg SILICA PER CUBIC METER OF AIR DIVIDED BY THE

PERCENT S102 AVERAGED OVER AN EIGHT HOUR WORK SHIFT AND FOR TOTAL DUST IS 30 mg/m³ DIVIDED BY THE PERCENT S102 AVERAGED OVER AN EIGHT HOUR WORK SHIFT.

EFFECTS OF OVEREXPOSURE: WITHOUT PROPER RESPIRATOR AND VENTILATION CONTROLS PROLONGED INHALATION OF DUST OVER A PERIOD OF YEARS WILL CAUSE SILICOSIS AND LUNG CANCER.

ACUTE OVER EXPOSURE: PRODUCT IS ALKALINE AND CAN IRRITATE THE SKIN AND EYES, AS WELL AS THE MUCOUS MEMBRANES.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN.

SKIN: IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

INGESTION: IMMEDIATELY SEEK MEDICAL ADVICE. GIVE MILK OR EGG WHITE BEATEN WITH WATER UNTIL VOMIT FLUID IS CLEAR. IF VOMITING DOES NOT OCCUR, INDUCE VOMITING BY GAGGING THE VICTIM. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

WASTE DISPOSAL METHOD: DISPOSE AS A NON HAZARDOUS WASTE, IN COMPLIANCE WITH LOCAL AND FEDERAL REGULATIONS. NOT CONSIDERED A HAZARDOUS WASTE BY THE EPA (RCRA).

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: SWEEP UP--AVIOD CREATING EXCESSIVE DUST. WEAR APPROVED MSHA/NIOSH RESPIRATORS. DO NOT WASH DOWN DRAINS.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: CRYSTALLINE SILICA (RESPIRABLE DUST) MUST BE WITHIN CURRENT OSHA STANDARDS:mg SILICA PER CUBIC METER OF AIR DIVIDED BY THE PERCENT S102 AVERAGED OVER AN EIGHT HOUR WORK SHIFT AND FOR TOTAL DUST IS 30 mg /m³ DIVIDED BY THE PERCENT S102 AVAGE OVER AN EIGHT HOUR WORK SHIFT.

RESPIRATORY: MSHA/NIOSH APPROVED RESPIRATOR 3M9900 OR EQUIVALENT.

EYES:CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION, OR INJURY.

GLOVES: RUBBER GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE RE-USE

OTHER HANDLING AND STORAGE REQUIREMENTS: STORE IN AIR TIGHT CONTAINERS OR POLY LINED BAGS IN A COOL DRY AREA. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL.

HMIS HAZARD RATING:

	NPCA-HMIS		NFPA 704
KEY			
HEALTH	2	2	4=SEVERE
FLAMMABILITY	0	0	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT
			0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL IT'S INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY:

DARRYL F. MANUEL

TITLE:

PRESIDENT

COMPANY:

VEXCON CHEMICALS

ADDRESS:

7240 STATE RD. PHILA., PA. 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN