



**HAZARD RATING**

4=EXTREME  
3=HIGH  
2=MODERATE  
1=SLIGHT  
0=INSIGNIFICANT

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>REACTIVITY</b>	<b>0</b>

**MATERIAL SAFETY DATA SHEET**  
**VEXCON NO. OP140**

**GENERAL INFORMATION**

**PRODUCT IDENTIFICATION:** STARSEAL® EF STRIPPER  
**VOC CONTENT:** NOT REQUIRED **CATEGORY:** NOT REQUIRED  
**COMMON NAME:** SOLVENT CONCRETE STRIPPER  
**DOT SHIPPING NAME:** IN CONTAINERS LESS THAN OR GREATER THAN 119 GALS: (NON REGULATED)  
**HEALTH AND SAFETY:** COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT.

**SECTION I**

**MANUFACTURER:** VEXCON CHEMICALS  
**EMERGENCY NO:** 1-800-858-2828  
**CHEMTREC NO:** 1-800-424-9300  
**TELEPHONE NO:** 1-215-332-770  
**ADDRESS:** 7240 STATE RD., PHILA., PA. 19135  
**PREPARED:** FEBRUARY 1999  
**UPDATED:** DECEMBER 2007  
**PREPARED BY:** DARRYL F. MANUEL / PRESIDENT

**SECTION II HAZARDOUS INGREDIENTS**

<b>MATERIAL OR COMPONENTS</b>	<b>CAS. NO.</b>	<b>HAZARD DATA</b>	<b>UN#</b>
PINE OIL	8002-09-3	NOT ESTB.	1272
SOYA OIL			
ATTAPULGITE CLAY	12174-11-7	ND	

**SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS**

**BOILING POINT,** 760 mm Hg: 310-428° F **MELTING POINT:** N/A  
**SPECIFIC GRAVITY** 0.948 **VAPOR PRESSURE:** 1.5 mm Hg @20C  
**VAPOR DENSITY (AIR=1):** 4.0 **SOLUBILITY IN H2O % BY WT:** MISCABLE  
**EVAPORATION RATE (BUOH=1):** .1PH (AS IS): 8.5 **PH (1% SOLN):** N/A  
**APPEARANCE AND ODOR:** PALE YELLOW LIQUID WITH SWEET PINE ODOR

**SECTION IV FIRE AND EXPLOSION DATA**

**FLASH POINT: (TEST METHOD):** 235° F TCC  
**AUTOIGNITION TEMPERATURE:** ND  
**FLAMMABLE LIMITS IN AIR: % BY VOL:** ND **LOWER:** 0.7 **UPPER:** 6.0  
**EXTINGUISHING MEDIA:** FOAM, DRY CHEMICAL, CO2, WATER FOG OR FIRE FIGHTING: USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. USE FOAM, DRY CHEMICAL, OR WATER SPRAY TO EXTINGUISH FIRE. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER. THE USE OF SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS. SEE ALSO SECTION IX.  
**GENERAL HAZARD:** COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE, SOLDER DRILL GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER ,OR PROPERLY DISPOSED OF.  
**ELECTROSTATIC ACCUMULATION HAZARD:** USE PROPER GROUNDING  
**UNUSUAL FIRE AND EXPLOSION HAZARD** KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.

**SECTION V REACTIVITY DATA**

**CONDITIONS CONTRIBUTING TO INSTABILITY:** PRODUCT IS STABLE  
**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS. STRONG ACIDS OR BASES AND SELECTED AMINES.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.  
**CONDITIONS CONTRIBUTING TO HAZARD POLYMERIZATION:** N/A WILL NOT OCCUR.

## SECTION VI HEALTH HAZARD INFORMATION

### INGESTION/INHALATION: TLV 50-100 ppm ESTIMATED FROM SIMILAR PRODUCTS

**ACUTE OVEREXPOSURE:** ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS; MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

### EMERGENCY AND FIRST AID PROCEDURES:

**EYES:** FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.

**SKIN:** WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.

**INHALATION:** MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION

## SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. DISPOSAL OF RESIDUAL MATERIAL, EITHER IN LIQUID FORM OR ABSORBED WITH CLAY OR SAND, MUST BE DONE IN COMPLIANCE WITH WITH EPA, STATE, AND LOCAL REGULATIONS.

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**LAND SPILL:** ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL, IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS IMPLEMENT CLEANUP PROCEDURES: FOR LARGE SPILL IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST .RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

**WATER SPILL:** REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSENTS MAY BE USED IN ON-CONFINED WATERS. CONSULT AN EXPERT DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

## SECTION VIII CONTROL MEASURES

**VENTILATION REQUIREMENTS** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** CHEMICAL CARTRIDGE RESPIRATOR; HALF MASK ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

**EYES:** CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

**GLOVES:** IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

**OTHER CLOTHING AND EQUIPMENT :** TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS ARE A RECOMMENDATION WHEN WORKING WITH THIS PRODUCT. AVAILABILITY OF EYE WASHES & SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

## SECTION IX SPECIAL PRECAUTIONS

### PRECAUTIONARY STATEMENTS:

**FIRE FIGHTING:** WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR.

**HMIS HAZARD RATINGS:** THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NEPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

### HMIS HAZARD RATINGS:

	NPCA-HMIS	NFPA 704	KEY
HEALTH	1	1	4=SEVERE
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT
			0=MINIMAL

## SECTION X REGULATORY INFORMATION

**TSCA:** THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN VARIABLE COMPOSITION BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 80541-3.

**CERCLA:** IF THIS PRODUCT IS ACCIDENTALLY SPILLED, IT IS NOT SUBJECT TO ANY SPECIAL REPORTING UNDER THE REQUIREMENTS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA). WE RECOMMEND YOU CONTACT LOCAL AUTHORITIES TO DETERMINE IF THERE MAY BE OTHER LOCAL REPORTING REQUIREMENTS.

**SARA TITLE III:** UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPER FUND AMENDMENTS AND REAUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES.

### DELAYED HEALTH, FIRE.

THIS PRODUCT DOES NOT CONTAIN SECTION 313 REPORTABLE INGREDIENTS.

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL IT'S INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

### PREPARED BY:

DARRYL MANUEL

### TITLE:

PRESIDENT

### COMPANY:

VEXCON CHEMICALS

### ADDRESS:

7240 STATE RD., PHILA., PA. 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN