



VEXCON
CHEMICALS, INC.

Concrete solutions for architects, engineers and builders since 1974
888-839-2661 | sales@vexcon.com | 7240 State Road | Philadelphia, PA 19135 vexcon.com

CERTI-VEX® CONCRETE REMOVER

CLEAN AND MAINTAIN CONSTRUCTION EQUIPMENT

DESCRIPTION

CERTI-VEX CONCRETE REMOVER is a premium, chemically active concrete equipment cleaning and maintenance treatment. Made from virgin oil stock and proprietary concrete softening and removal compounds, the product will effectively soften concrete build up for quick cleaning of hardened concrete and when applied as a treatment will prevent concrete bonding and buildup.

Certi-Vex Concrete Remover is ideal for all residual applications ranging from trucks, slides, trowels, power screeds, scaffolding, paving and forming equipment where fresh concrete has been allowed to adhere or as part of a maintenance program to prevent concrete from bonding to treated surfaces.

Certi-Vex Concrete Remover reacts with the cement in fresh set concrete to prevent continuing hardening of the paste. By applying in accordance with directions, the concrete surface will become soft, allowing easy removal of concrete attached to metal concrete construction equipment.

BENEFITS

- Meets all clean air VOC standards through out the US
- Zero VOC
- Maximum protection of metal concrete construction equipment
- Non staining
- Excellent anti-stick properties for metal
- Minimum labor-just spray or brush on concrete

APPLICATION TO REMOVE EARLY SET CONCRETE

- Remove loose concrete, with power washer or by mechanical means.
- Apply a test area prior to full application to determine application rate and over all effectiveness.
- Mix before use
- Apply with low pressure sprayer, brush or roller
- Allow to sit on concrete for 1-2 hours
- Wire brush surface or abrade surface to remove the paste like mixture of broken down concrete.
- Additional applications may be required to remove heavier build up or longer cured concrete. Product works best on 1-3 day old concrete.
- Power wash and air dry metal after washing prior to applying a maintenance coat, see Application as a Maintenance Coat section, of Certi-Vex Concrete Remover to prevent future buildup.

APPLICATION AS A MAINTAINANCE TREATMENT

- Remove previous buildup of concrete, rust, scale and dirt with Certi-Vex Concrete Remover. See Application To Remove Early Set Concrete.
- Apply a test area prior to full application to determine application rate and over all effectiveness.
- Allow surface to air dry
- Mix before use
- Apply with low pressure sprayer, brush or roller
- Certi-Vex Concrete Remover can be effective for up to three weeks before concrete is poured. It is also recommended that metal be treated with Certi-Vex Concrete Remover between each pour and before long periods of idleness or storage.

SPECIAL NOTES

- If left out in freezing temperatures, apply a heater to slightly warm up for better spraying.
- Do not use as form release treatment
- Not recommended for removal of concrete after 28 days of cure.
- Coat Uniformly-Leave No Gaps
- Shelf life: If properly stored in its original sealed container, three years from date of manufacture. Rotate your stock.

COVERAGE

400-500 sq.ft./gal. Coverage will vary depending surface, build up and age of concrete.

SPECIFICATIONS/COMPLIANCE

- VOC Content: 0 gr./liter
Meets all clean air standards through out the US:
 - USEPA AIM- Form Release Compound
 - OTC- Form Release Compound
 - CARB- Form Release Compound
 - SCAQMD- Bond Breaker

PACKAGING

Certi-Vex Concrete Remover is available in 55-gallon drums, 5-gallon pails and 1-gallon containers. Contact Vexcon directly to discuss your packing requirements.

VITAL STATISTICS

- Flash Point: 375° F (191° C) Min. PMCC
- Autoignition Temp: 600° F (315° C)
- Extinguishing Media: Foam, Dry chemical, CO₂, Water Fog or spray

HEALTH AND SAFETY

- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.

Vexcon MSDS #OP145 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product it is advisable to obtain a copy of the MSDS, #OP145 from your distributor or by contacting Vexcon Chemicals.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals or our distributors.

- vexcon.com
- techservice@vexcon.com
- customerservice@vexcon.com
- sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.