

HAZARD RATING
 4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

| | |
|---------------------|----------|
| HEALTH | 2 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |

MATERIAL SAFETY DATA SHEET VEXCON NO. PV124

GENERAL INFORMATION

PRODUCT IDENTIFICATION: PAVER RENUE HIGH GLOSS
VOC CONTENT: <700 GRAMS/LITER OR <5.83#/GAL
CATEGORY: CURE AND SEAL
COMMON NAME: STYRENE ACRYLATE COPOLYMER IN AROMATIC / ALIPH. SOLVENT
DOT SHIPPING NAME:
 IN CONTAINERS LESS THAN 119 GALS:
 PAVER RENUE HIGH GLOSS (NON-REGULATED)
 IN CONTAINERS GREATER THAN 119 GALS:
 COMBUSTIBLE LIQUID, N.O.S. (AROMATIC SOLVENT), 3, NA 1993, III
FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:
 RQ (AROMATIC SOLVENT) RESIN SOLUTION, FLAMMABLE, 3, UN1866, III
HEALTH AND SAFETY: COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN CONFINED AREA.

SECTION I

MANUFACTURER: VEXCON CHEMICALS, INC.
ADDRESS: 7240 STATE RD., PHILA., PA 19135 USA
EMERGENCY NO: 1-800-858-2828
TELEPHONE NO: 1-215-332-7709
CHEMTREC NO: 1-800-424-9300
PREPARED: MAY 1996
UPDATED: MARCH 2010
PREPARED BY: DARRYL F. MANUEL, PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

| MATERIAL OR COMPONENTS | CAS NO. | % | HAZARD DATA | UN# |
|---|------------|---------|---|------|
| STYRENE ACRYLATE POLYMER | 25036-16-2 | 15-30 % | ND | |
| SOLVENT NAPHTHA (Petroleum), LIGHT AROMATIC | 64742-95-6 | 20-30 % | TLV 50 PPM OSHA HAZARD: COMBUSTIBLE | 1268 |
| WHICH CONTAINS | | | | |
| PETROLEUM HYDROCARBONS | 8052-41-3 | 40-70 % | OSHA PEL: 2900 mg/m3 ACGIH TLV: 525 mg/m3 OR 100 ppm | 1225 |
| TRIMETHYL BENZENE | 95-63-6 | 10 % | OSHA PEL: NE ACGIH TLV: 25ppm | 2325 |
| THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS: | | | | |
| COMPONENT | CAS NO. | MAX % | | |
| TRIMETHYL BENZENE | 95-63-6 | 10 % | OSHA PEL: NE ACGIH TLV: 25ppm | 2325 |

SECTION III PHYSICAL / CHEMICAL CHARACTERISTICS

| | |
|---|-----------------------------------|
| BOILING POINT: (760mmHg) 310-405°F / 154-207°C | MELTING POINT: N/A |
| VAPOR PRESSURE: 3.1 mmHg@68°F/20°C | VAPOR DENSITY (AIR=1): 4.9 |

| | |
|--|---|
| SOLUBILITY IN H2O % BY WT: INSOLUBLE | % VOLATILES BY VOL: 65-85% |
| EVAPORATION RATE (BuAc=1): 0.12 | SPECIFIC GRAVITY (H2O=1) 0.894 |
| pH (AS IS) N/A | pH (1% SOLN) N/A |
| APPEARANCE AND ODOR: | WATER WHITE LIQUID WITH PAINT SOLVENT ODOR. (MAY CONTAIN FUGITIVE RED DYE). |

SECTION IV FIRE AND EXPLOSION DATA

| | |
|--|--|
| FLASH POINT: (TEST METHOD) | 41°C / 106°F (TCC) |
| AUTOIGNITION TEMP: | 245°C / 473°F |
| FLAMMABLE LIMITS IN AIR, % BY VOL: | LOWER: 0.5% UPPER: 6.0% |
| EXTINGUISHING MEDIA: | FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY REGULAR FOAM, CARBON DIOXIDE OR DRY CHEMICAL. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. |
| GENERAL HAZARD: | COMBUSTIBLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF. |
| ELECTRO-STATIC ACCUMULATION HAZARD: | USE PROPER GROUNDING |
| UNUSUAL FIRE AND EXPLOSION HAZARD: | VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. |
| SPECIAL FIRE FIGHTING PROCEDURES: | THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP. |

SECTION V REACTIVITY DATA

| | |
|---|---|
| CONDITIONS CONTRIBUTING TO INSTABILITY: | THIS PRODUCT IS STABLE. |
| INCOMPATIBILITY: | THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES. THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND HYDROCARBON VOLATILES. |
| HAZARDOUS DECOMPOSITION PRODUCTS: | |
| CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: | N/A WILL NOT OCCUR |

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

ROUTES OF EXPOSURE:

| | |
|---------------------------------|--|
| INHALATION: | THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. AR 100 AND STODDARD SOLVENT COMPONENTS. |
| SKIN CONTACT: | THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AR 100 AND STODDARD SOLVENT COMPONENTS. |
| SKIN ABSORPTION: | THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AR 100 AND STODDARD SOLVENT COMPONENTS. |
| EYE CONTACT: | THIS PRODUCT MAY BE AN EYE IRRITANT. AR 100 AND STODDARD SOLVENT COMPONENTS. |
| INGESTION / INHALATION | SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION. |
| EFFECTS OF OVEREXPOSURE: | TLV 50 ppm ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES. |
| ACUTE OVEREXPOSURE: | ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEBAT THE SKIN POSSIBLY CAUSING DERMATITIS. |

EMERGENCY AND FIRST AID PROCEDURES:

| | |
|--------------------|---|
| EYES: | FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION. |
| SKIN: | WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS. |
| INHALATION: | MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. |
| INGESTION: | DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION. |

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL

AQUATIC TOXICITY (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE: FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYE: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS

(HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED/DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

OTHER HANDLING AND STORAGE REQUIREMENTS: KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMIS HAZARD RATINGS:

THIS INFORMATION IS FOR PEOPLE TRAINED IN:
NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA)
HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)
NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704)
IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

| VEXCON PAVER RENUE HIGH GLOSS | NPCA- HMIS | NFPA 704 | KEY |
|----------------------------------|---------------|-------------|------------|
| HEALTH | 2 | 2 | 4=SEVERE |
| FLAMMABILITY | 2 | 2 | 3=SERIOUS |
| REACTIVITY | 0 | 0 | 2=MODERATE |
| | | | 1=SLIGHT |
| | | | 0=MINIMAL |

SECTION X REGULATORY INFORMATION

TSCA: THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6.

CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 800-424-8802. **THE REPORTABLE SPILL QUANTITY OF THIS PRODUCT IS 5,000 POUNDS. THIS PRODUCT CONTAINS: XYLENE, ETHYLBENZENE, CUMENE, AND TRIMETHYL BENZENE**

SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: **DELAYED HEALTH, FIRE**

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

FEDERAL:

FDA:

USDA:

CERCLA / RQ: 5000 POUNDS

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? **YES**

PREPARED BY DARRYL MANUEL / PRESIDENT

COMPANY: VEXCON CHEMICALS, INC.

ADDRESS: 7240 STATE RD., PHILA., PA 19135 USA

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN.