



PAVER RENEU STRIPPER

HEAVY BODIED STRIPPER USED TO REMOVE A VARIETY OF COATINGS • ECONOMICAL

DESCRIPTION

CERTI-VEX® CONCRETE STRIPPER strips concrete floors and other concrete surfaces with relative ease. Removes many types of coatings from concrete such as sealers, curing compounds, urethanes, and epoxies in addition to floor waxes and adhesives. After use, Paver Renew Stripper is emulsifiable with water and general cleaners to yield a stripped concrete surface that is clean and ready for subsequent treatments. Use **Paver Renew Stripper Vertical** for vertical applications.

APPLICATION

- Do not thin Paver Renew Stripper. It is supplied at the proper consistency for most effective action.
- Scrape or brush the surface to be stripped with a wire brush or broom to remove loose and flaking coating or residual dirt.
- Mix well prior to each application to a uniform consistency.
- Apply Paver Renew Stripper brush, squeegee, roller or airless sprayer in a heavy uniform application.
- Allow the stripper to soften the coating but do not allow the surface to dry.
- Keep wet with Paver Renew Stripper.
- Once a gel has formed, remove the stripper and softened coatings with a floor machine equipped with nylon bristle brush, steel wool, stone media, or by scraping. During removal, apply additional Paver Renew Stripper to further soften the coating.
- Rinse area with water. Make a second application if needed.
- After removal of the coating, clean the surface with **Paver Renew Degreaser & Cleaner**.
- **Application Rate:** 75-150 sq. ft. per gallon depending on thickness and type of coating to be removed.
- Apply a test patch before any protective treatment application.

PROTECT

After thorough cleaning, finish your surface with one of Vexcon's premium concrete protection products. Contact Vexcon for product recommendations.

SPECIFICATIONS/COMPLIANCE

- CSI reference: 03 01 30.51, 03 01 40.51

PACKAGING

Paver Renew Stripper is available in 55-gallon drums, 5-gallon pails and 1-gallon containers. Contact Vexcon to discuss your customized packaging requirements.

SPECIAL NOTES

- Do not apply to plastic, PVC or rubber
- Protect all surrounding plants and vegetation with a plastic drop cloth.
- Surface area should be tested to prevent damage to substrate.
- If applying out doors or interior hot or dry conditions cover the area with light plastic drop cloth.
- Do not allow the product to dry on the surface. Keep wet by applying additional material.
- Do not thin Paver Renew Stripper. It is supplied at the proper consistency for most effective action.
- If using a brush to apply the product do not apply like a paint.
- If properly stored in its original sealed container, three years from date of manufacture. May require mixing. Rotate your stock.
- Proper application of Vexcon material is the responsibility of the installer or user. Telephone consultation and/or field visits by Vexcon personnel are for the sole purpose of making technical recommendations only, and not for providing quality control or supervision on location.

VITAL STATISTICS

- | | |
|-----------------------|--|
| • Flash Point | 108° F (>42° C) TCC |
| • Boiling Point | 322-340° F (161-171° C) |
| • Autoignition Temp | 894°F (479°C) |
| • Extinguishing Media | Foams, Dry Chemical, CO ₂ , Water fog or spray. |

HEALTH AND SAFETY

- Caution, slippery when applied. Use care when walking. Spread sand for traction.
- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Aspiration of materials into the lungs can cause chemical pneumonitis, which can be fatal.
- Use of respirators is advised when using this product in confined areas.

The stripper solution and/or materials may be classified as a hazardous material for purposes of disposal. This material should be kept in a separate container and local federal rules for disposal must be followed. Vexcon MSDS PV152 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product, it is advisable to obtain a copy of the MSDS from your distributor or by contacting Vexcon Chemicals.

CONTACT US@

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly, or our distributors.

- | | |
|--|--|
| • www.vexcon.com | • sales@vexcon.com |
| • techservice@vexcon.com | • Voice: 888.839.2661 |
| • customerservice@vexcon.com | • Fax: 215.332.9997 |

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.