

HAZARD RATING  
 4=EXTREME  
 3=HIGH  
 2=MODERATE  
 1=SLIGHT  
 0=INSIGNIFICANT

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>





SAFETY DATA SHEET  
 VEXCON NO. PS105  
**POWERSEAL WEATHERPROOF**  
**100 & 500**

**GENERAL INFORMATION**

<b>PRODUCT IDENTIFICATION:</b> <b>POWERSEAL WEATHERPROOF 100 &amp; 500</b>	
<b>VOC CONTENT:</b> <100 GRAMS/LITER OR <0.83 #/GAL.	
<b>CATEGORY:</b> WATERPROOFING CONCRETE/MASONRY SEALER	
<b>COMMON NAME:</b> ALKOXYLSILANE EMULSION, WATER REPELLENT	
<b>MANUFACTURER:</b>	<b>VEXCON CHEMICALS, INC.</b>
<b>ADDRESS:</b>	7240 STATE RD., PHILA., PA 19135 USA
<b>EMERGENCY NO:</b>	1-800-858-2828 (PolySat)
<b>TELEPHONE NO:</b>	1-215-332-7709 (Vexcon)
<b>CHEMTREC NO:</b>	1-800-424-9300 (Chemtrec)
<b>PREPARED:</b>	FEBRUARY 1996
<b>UPDATED:</b>	AUGUST 2014
<b>PREPARED BY:</b>	DARRYL F. MANUEL, PRESIDENT

**SECTION II – HAZARD IDENTIFICATION**

**DOT SHIPPING NAME:**  
 SHIPPING NAME / HAZARD CLASS / UN NUMBER / PACKING GROUP  
 IN CONTAINERS LESS THAN AND GREATER THAN 119 GALS: IN ALL MODES  
 OF DOMESTIC AND INTERNATIONAL TRANSPORTATION  
**(NON-REGULATED)**  
**HEALTH AND SAFETY** COMBUSTIBLE LIQUID: THIS  
 PRODUCT IS A SOLVENT IN WATER EMULSION. ALL  
 PRECAUTIONS PROVIDED ARE FOR THE SOLVENT  
 PORTION OF WHICH THIS CONTAINS **LESS THAN 5%**.  
 COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE  
 VENTILATION. IF SWALLOWED, DO NOT INDUCE  
 VOMITING. USE OF SOLVENT RESISTANT GLOVES,  
 GOGGLES, AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN  
 HANDLING THIS PRODUCT. FLASH POINT: SOLVENT H2O EMULSION 245  
 DEGREES F (NON-FLAMMABLE). **KEEP FROM FREEZING.**

**SECTION III HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
OCTYLTRIETHOXY SILANE	2943-75-1	5-20%	NONE	NNONE
STODDARD SOLVENT	8052-41-3	1-5%	ACGIH TLV: 100 ppm, 525 mg/m3 (TWA) OSHA PEL: 500 ppm, 2900 mg/m3 (TWA) NIOSH REL: 350 mg/m3 (TWA)	1255
UNIDENTIFIED SILOXANE IMPURITIES	NONE	TRACE	NOT ESTABLISHED	NONE
WATER	7732-18-5	BALANCE	NONE	NONE

**SECTION IV FIRST AID MEASURES**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE**

<b>ROUTES OF EXPOSURE:</b>	
<b>INHALATION:</b>	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. STODDARD SOLVENT COMPONENT.
<b>SKIN CONTACT:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. STODDARD SOLVENT COMPONENT.
<b>SKIN ABSORPTION:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. STODDARD SOLVENT COMPONENT.
<b>EYE CONTACT:</b>	THIS PRODUCT MAY BE AN EYE IRRITANT. STODDARD SOLVENT COMPONENT.
<b>INGESTION / INHALATION</b>	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>EFFECTS OF OVEREXPOSURE:</b>	<b>TLV 50 ppm</b> STODDARD SOLVENT COMPONENT. ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
<b>ACUTE OVEREXPOSURE:</b>	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.

**EMERGENCY AND FIRST AID PROCEDURES:**

<b>EYES:</b>	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>SKIN:</b>	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
<b>INHALATION:</b>	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. <b>NOTE:</b> THIS MATERIAL RELEASES <b>ETHYL ALCOHOL</b> UPON HYDROLYSIS. ETHYL ALCOHOL CAUSES OPTIC NEUROPATHY, METABOLIC ACIDOSIS AND RESPIRATORY DEPRESSION. SIGNS AND SYMPTOMS OF OVEREXPOSURE INCLUDE HEADACHE, BLURRED VISION, CONSTRICTED VISUAL FIELDS, SHORTNESS OF BREATH, DIZZINESS AND VERTIGO. INGESTION OF ETHYL ALCOHOL MAY LEAD TO BLINDNESS OR DEATH.
<b>INGESTION:</b>	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

**SECTION V FIREFIGHTING MEASURES**

<b>EXTINGUISHING MEDIA:</b>	EXCLUDE AIR. FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES.
<b>GENERAL HAZARD:</b>	COMBUSTIBLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN

	INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
<b>ELECTRO-STATIC ACCUMULATION HAZARD:</b>	USE PROPER GROUNDING
<b>UNUSUAL FIRE AND EXPLOSION HAZARD:</b>	COMBUSTIBLE VAPORS MAY ACCUMULATE IN THE CONTAINER HEADSPACE ON FORMATION OF HYDROLYSIS BYPRODUCTS. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.
<b>SPECIAL FIRE FIGHTING PROCEDURES</b>	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP. USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

### SECTION VI ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**LAND SPILL:** ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

**WATER SPILL:** REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

### SECTION VII HANDLING AND STORAGE

**PRECAUTIONARY STATEMENTS:** PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**FIRE FIGHTING:** WATER MAY BE HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

### SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

**VENTILATION REQUIREMENTS:** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

**EYES:** CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

**GLOVES:** THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

**OTHER CLOTHING AND EQUIPMENT:** TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

### SECTION IX SPECIAL PRECAUTIONS

<b>BOILING POINT:</b> (760mmHg) <b>210°F / 98°C</b>	<b>MELTING POINT:</b> -40°C ./ -40°F (Stoddard Solvent)
<b>VAPOR PRESSURE:</b> 5 mmHg@68°F/25°C (Stoddard solvent)	<b>VAPOR DENSITY (AIR=1):</b> 4.8 (Stoddard solvent) HEAVIER THAN AIR
<b>SOLUBILITY IN H2O % BY WT:</b> 100%	<b>% VOLATILES BY VOL:</b> 100%
<b>EVAPORATION RATE (BuAc=1):</b> 0.1 SLOW (MINERAL SPIRITS)	<b>SPECIFIC GRAVITY (H2O=1)</b> 0.982
<b>pH (AS IS)</b> 5-6 TYPICAL	<b>pH (1% SOLN)</b> N/A
<b>APPEARANCE AND ODOR:</b> WHITE TO YELLOW CLOUDY EMULSION WITH SLIGHT PAINT SOLVENT ODOR	
<b>FLASH POINT:</b> (TEST METHOD)	<b>118°C / 245°F (TCC)</b>
<b>AUTOIGNITION TEMP:</b>	232°C / 450°F (STODDARD SOLVENT)
<b>FLAMMABLE LIMITS IN AIR, % BY VOL:</b>	LOWER: 0.8% UPPER: 6.0% (STODDARD SOLVENT)

### SECTION X STABILITY AND REACTIVITY

<b>CONDITIONS CONTRIBUTING TO INSTABILITY:</b>	THIS PRODUCT IS STABLE.
<b>INCOMPATIBILITY:</b>	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
<b>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:</b>	N/A WILL NOT OCCUR

**SECTION XI TOXICOLOGICAL INFORMATION**

STODDARD SOLVENT

ROUTE OF EXPOSURE	CONCLUSION/REMARKS	
INHALATION	TOXICITY	MINIMALLY TOXIC. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
	IRRITATION	NEGLECTIBLE HAZARD AT AMBIENT/NORMAL HANDLING TEMPERATURES
INGESTION	TOXICITY: LD50 >5000 mg/kg	MINIMALLY TOXIC. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
SKIN	TOXICITY: LD50 >3160 mg/kg	MINIMALLY TOXIC. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
	IRRITATION	MAY DRY THE SKIN LEADING TO DISCOMFORT AND DERMATITIS. BASED N TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS
EYE	IRRITATION	MAY CAUSE MILD, SHORT-LASING DISCOMFORT TO EYES. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS.

**SECTION XII ECOLOGICAL INFORMATION**

STODDARD SOLVENT

**THIS INFORMATION GIVEN IS BASED ON DATA AVAILABLE FOR THE MATERIALS, THE COMPONENTS OF THE MATERIAL AND SIMILAR MATERIALS.**

<b>ECOTOXICITY</b>	MATERIALS – EXPECTED TO BE TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT
<b>MOBILITY</b>	MATERIAL- HIGHLY VOLATILE, WILL PARTITION RAPIDLY TO AIR. NOT EXPECTED TO PARTITION TO SEDIMENT AND WASTEWATER SOLIDS.
<b>PERSISTENCE AND DEGRADABILITY</b>	
<b>BIODEGRADATION</b>	MATERIAL- EXPECTED TO BE INHERENTLY BIODEGRADABLE
<b>HYDROLYSIS</b>	MATERIAL – TRANSFORMATION DUE TO HYDROLYSIS NOT EXPECTED TO BE SIGNIFICANT.
<b>PHOTOLYSIS</b>	MATERIAL – TRANSFORMATION DUE TO PHOTOLYSIS NOT EXPECTED TO BE SIGNIFICANT
<b>ATMOSPHERIC OXIDATION</b>	MATERIAL – EXPECTED TO DEGRADE RAPIDLY IN AIR

**SECTION XIII DISPOSAL CONSIDERATIONS**

**AQUATIC TOXICITY (E.G. 96 HR. TLM):** DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT, TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND

FILL SITES ARE AVAILABLE.

**SECTION XIV TRANSPORTATION INFORMATION**

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	GROUND	NON REGULATED	NON REGULATED	NON REGULATED	NA
IATA	AIR	NON REGULATED	NON REGULATED	NON REGULATED	NA
IMDG	OCEAN	NON REGULATED	NON REGULATED	NON REGULATED	NA
<b>MARINE POLLUTANT:</b>		THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B)			

**SECTION XV REGULATORY INFORMATION**

**TSCA:** THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 8052-41-3 (STODDARD SOLVENT).

**CERCLA:** IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675.

**NO REPORTABLE SPILL QUANTITY (RQ) HAS BEEN ESTABLISHED FOR THIS PRODUCT (STODDARD SOLVENT).**

**SARA TITLE III:** UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: ACUTE, CHRONIC, FIRE

**ADDITIONAL REGULATORY CONCERNS:** (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)  
FEDERAL / FDA / USDA:

**MARINE POLLUTANTS:** NO. THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B).

**CERCLA / RQ: NONE ESTABLISHED.**  
THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A).

**TSCA:** IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? **YES**

**SECTION XVI OTHER INFORMATION**

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

**HMIS HAZARD RATINGS:**

THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			<b>KEY</b>
			4 -- SEVERE
<b>POWERSEAL WEATHERPROOF 100 &amp; 500</b>	<b>NPCA-HMIS</b>	<b>NFPA 704</b>	3 -- SERIOUS
<b>HEALTH</b>	<b>1</b>	<b>1</b>	2 -- MODERATE
<b>FLAMMABILITY</b>	<b>1</b>	<b>1</b>	1 -- SLIGHT
<b>REACTIVITY</b>	<b>0</b>	<b>0</b>	0 -- MINIMAL