

HAZARD RATING 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT	<b>HEALTH</b>	<b>1</b>
	<b>FLAMMABILITY</b>	<b>1</b>
	<b>REACTIVITY</b>	<b>0</b>


SAFETY DATA SHEET  
 VEXCON NO. CP099  
**POWERCOAT ONE CLEAR**

**SECTION I - GENERAL INFORMATION**

<b>PRODUCT IDENTIFICATION:</b> <b>POWERCOAT ONE CLEAR</b>	
<b>VOC CONTENT:</b>	<340 GR/LITER OR <2.83 #/GAL
<b>CATEGORY:</b>	<b>INDUSTRIAL MAINTENANCE COATING</b>
<b>COMMON NAME:</b>	<b>STYRENE ACRYLATE EPOXY EMULSION</b>
<b>MANUFACTURER:</b>	<b>VEXCON CHEMICALS, INC</b>
<b>ADDRESS</b>	7240 STATE RD, PHILADELPHIA, PA 19135
<b>EMERGENCY NO:</b>	800.858.2828 (PolySat Inc)
<b>TELEPHONE NO:</b>	215.332.7709 (Vexcon)
<b>CHEMTREC NO:</b>	800.424.9300 (CCN# 23822)
<b>PREPARED:</b>	DECEMBER 1999
<b>UPDATED:</b>	JANUARY 2017
<b>PREPARED BY:</b>	DARRY F. MANUEL , PRESIDENT

(AR100) THE AROMATIC SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:				
COMPONENT	CAS NO.	MAX %	HAZARD DATA	UN#
1,2,4-TRIMETHYL BENZENE (PSEUDOCUMENE)	95-63-6	<32.0%	OSHA PEL: NE ACGIH TLV: 25ppm (TWA)	1993 (FLAMMABLE LIQUIDS, N.O.S)
XYLENES	1330-20-7	<2.2%	OSHA Z1 100ppm (TWA) ACGIH TLV 100ppm (TWA) NIOSH REL 100 ppm (TWA)	1307 (XYLENES)
CUMENE	98-82-8	<1.1%	OSHA Z1 50ppm (TWA) ACGIH TLV 50ppm (TWA)	1918 (ISOPROPYL BENZENE)

**SECTION II – HAZARD IDENTIFICATION**

<b>CLASSIFICATION OF MIXTURE</b> ASPIRATION - CATEGORY 1 EYE IRRITATION – CATEGORY 2B SKIN IRRITATION – CATEGORY 2 SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE (NARCOTIC EFFECTS) – CATEGORY 3
<b>SINGLE WORD:</b> WARNING
<b>HAZARD STATEMENT:</b> UNDER NORMAL CONDITIONS OF USE, THIS PRODUCT IS NOT CONSIDERED HAZARDOUS ACCORDING TO REGULATORY GUIDELINES.
<b>PRECAUTIONARY STATEMENT:</b> UNDER NORMAL CONDITIONS OF INTENDED USE, THIS PRODUCT DOES NOT POSE A RISK TO HEALTH. EXCESSIVE EXPOSURE MAY RESULT IN EYE, SKIN OR RESPIRATOR IRRITATION. THIS PRODUCT IS AN ORGANIC LIQUID AND WATER EMULSION. PER NFPA 30 THIS MIXTURE WITH A FLASH POINT GREATER THAN 200 F IS A CLASS III B COMBUSTIBLE LIQUID. ALL PRECAUTIONS PROVIDED ARE FOR THE ORGANIC LIQUID PORTION OF WHICH THIS PRODUCT MAY CONTAIN AS LITTLE AS 10%. USE WITH ADEQUATE VENTILATION. DO NOT INDUCE VOMITING IF SWALLOWED. USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT. <b>KEEP FROM FREEZING.</b>


**SECTION IV FIRST AID MEASURES**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE**

ROUTES OF EXPOSURE:	
<b>INHALATION:</b>	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. AROMATIC 100 SOLVENT COMPONENT.
<b>SKIN CONTACT:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 SOLVENT COMPONENT.
<b>SKIN ABSORPTION:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 SOLVENT COMPONENT.
<b>EYE CONTACT:</b>	THIS PRODUCT MAY BE AN EYE IRRITANT. AROMATIC 100 SOLVENT COMPONENT.
<b>INGESTION / INHALATION</b>	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>EFFECTS OF OVEREXPOSURE:</b>	<b>TLV 50 ppm</b> AROMATIC 100 SOLVENT COMPONENT. ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
<b>ACUTE OVEREXPOSURE:</b>	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAIT THE SKIN POSSIBLY CAUSING DERMATITIS.

**SECTION III HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
STYRENE ACRYLATE EPOXY EMULSION	TRADE SECRET	30-40%	ND	NONE
SOLVENT NAPHTHA (Petroleum), LIGHT AROMATIC	64742-95-6	5-10%	TLV 50ppm OSHA HAZARD: COMBUSTIBLE LIQUID	1268
WATER	NA	BAL	NONE	NONE

**EMERGENCY AND FIRST AID PROCEDURES:**

<b>EYES:</b>	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>SKIN:</b>	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
<b>INHALATION:</b>	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
<b>INGESTION:</b>	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

**SECTION V FIREFIGHTING MEASURES**

<b>EXTINGUISHING MEDIA:</b>	FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY <b>REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY.</b> WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER.
<b>GENERAL HAZARD:</b>	CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. <b>STATIC DISCHARGE</b> - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCIDENTAL ELECTRICAL DISCHARGE. <b>"EMPTY" CONTAINERS</b> RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
<b>UNUSUAL FIRE AND EXPLOSION HAZARD:</b>	<u>NO UNUSUAL HAZARDS.</u> PRODUCT WILL BURN IF TEMPERATURE EXCEEDS BOILING POINT WATER MIX. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. <b>VAPOR IS HEAVIER THAN AIR</b> AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS <b>FREE OF HOT METAL</b> SURFACES AND OTHER SOURCES OF IGNITION.
<b>SPECIAL FIRE FIGHTING PROCEDURES</b>	THE USE OF <b>SELF-CONTAINED BREATHING APPARATUS</b> WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT <b>COOL WITH WATER SPRAY</b> IN ORDER TO PREVENT PRESSURE BUILD UP.

**SECTION VI ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** ELIMINATE SOURCES OF IGNITION (FLARES, FLAMES, PILOT LIGHTS, ELECTRICAL SPARKS). PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. DIKE SPILL AREA WITH SAND OR EARTH TO CONTAIN SPILLED LIQUID AND PREVENT SPREADING. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR WITH ANOTHER SUITABLE ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

**SECTION VII HANDLING AND STORAGE**

**PRECAUTIONARY STATEMENTS:** PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**FIRE FIGHTING:** WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

**SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION**

<b>VENTILATION REQUIREMENTS:</b> LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.
<b>RESPIRATORY (SPECIFY IN DETAIL):</b> THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.
<b>EYES:</b> CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.
<b>GLOVES:</b> THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.
<b>OTHER CLOTHING AND EQUIPMENT:</b> TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

**SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS**

<b>BOILING POINT: (760mmHg)</b> 100 C / 212 F (WATER)	<b>MELTING/FREEZING POINT:</b> -95 C, -139 F (WATER)
<b>VAPOR PRESSURE:</b> 17.5 mmHg@68°F/20°C (WATER)	<b>VAPOR DENSITY (AIR=1):</b> GREATER THAN AIR
<b>SOLUBILITY IN H2O % BY WT:</b> 100%	<b>% VOLATILES BY VOL:</b> 60-70%
<b>EVAPORATION RATE (BuAc=1):</b> SLOW 0.3 (WATER)	<b>SPECIFIC GRAVITY (H2O=1)</b> 1.002
<b>pH (AS IS):</b> 7-8 TYPICAL	<b>pH (1% SOLN):</b> N/A
<b>APPEARANCE AND ODOR:</b>	MILKY WHITE EMULSION WITH SOLVENT ODOR
<b>FLASH POINT:</b> (TEST METHOD)	<b>&gt;93°C / &gt;200°F (TCC)</b>
<b>AUTOIGNITION TEMP:</b>	479°C / 894°F (AR100)
<b>FLAMMABLE LIMITS IN AIR, % BY VOL:</b>	LOWER: 0.9% UPPER: 6.2% (AR100)

**SECTION X STABILITY AND REACTIVITY**

<b>CONDITIONS CONTRIBUTING TO INSTABILITY:</b>	THIS PRODUCT IS STABLE.
<b>INCOMPATIBILITY:</b>	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
<b>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:</b>	N/A WILL NOT OCCUR

**SECTION XI TOXICOLOGICAL INFORMATION**

<b>ACUTE TOXICITY:</b>	INHALATION	TOXICITY: DATA AVAILABLE	MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. BASED ON THESE DATA FOR THE MATERIAL
		IRRITATION; DATA AVAILABLE	MAY BE IRRITATING TO THE RESPIRATORY TRACT. THE EFFECTS ARE

			REVERSIBLE. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERAILS
	INGESTION	TOXICITY: LD50.3000mg/kg	MINIMALLY TOXIC. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS.
	SKIN	TOXICITY: LD50 >3160 mg/kg	MINIMALLY TOXIC. BASED ON TEST DATA FOR THE MATERIAL
		IRRITATIONS DATA AVAILABLE	MIKLY IRRITATION TO SKIN WITH PROLONGED EXPOSURE. BASED ON TEST DATA FOR THE MATERIAL
	EYE	IRRITATION DATA AVAILBLE	MAY CAUSE MILD, SHORT-LASTING DISCOMFORT TO EYES. BASE ON TEST DATAT FOR THE MATERIAL
<b>CHRONIC/OTHER EFFECTS</b>	FOR THE PROUDCT ITSELF: VAPOR /AEROSOL CONCENTRATIONS ABOVE RECOMMENDED EXPOSURE LEVELS ARE IRRITATING TO THE EYES AND RESPIRATORY TRACT, MAY CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS AND OTHER CENTRAL NERVOUS SYSTEMS EFFECTS INCLUDING DEATH. PROLONGED AND/OR REPEATED SKIN CONTACT WITH LOW VISCOSITY MATERIALS MAY DEFAT THE SKIN RESULTING IN POSSIBLE IRRITATION AND DERMATITIS. SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE LUNGS DURING INGESTIN OR FROM VOMITING MAY CAUSE CHEMICAL PHEUMONITIS OR PULMONARY EDEMA.		
	CONTAINS	CUMENE: REPEATED INHALATION EXPOSURE OF CUMENE VAPOR PRODUCED DAMAGE IN KIDNEY OF MALE RATS ONLY. THE EFFECTS ARE BELIEVED TO BE SPECIES SPECIFIC NAD ARE NOT RELEVANT TO HUMANS.	

### SECTION XII ECOLOGICAL INFORMATION

<b>ECOTOXICITY</b>	MATERIAL EXPECTED TO BE TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>MOBILITY</b>	MATERIAL HIGHLY VOLATILE, WILL PARTITION RAPIDLY TO AIR. NOT EXPECTED TO PARTITION TO SEDIMENT AND WASTEWATER SOLIDS.
<b>PERSISTENCE AND DEGRADABILITY</b>	
<b>BIODEGRADATION</b>	MATERIAL EXPECTED TO BE READILY BIODEGRADABLE
<b>HYDROLYSIS</b>	MATERIAL TRANSFORMATION DUE TO HYDROLYSIS NOT EXPECTED TO BE SIGNIFICANT.
<b>PHOTOLYSIS</b>	MATERIAL TRANSFORMATION DUE TO PHOTLYSIS NOT EXPECTED TO BE SIGNIFICANT.
<b>ATMOSPHERIC OXIDATION</b>	MATERIAL EXPECTED TO DEGRADE RAPIDLY IN AIR

### SECTION XIII DISPOSAL CONSIDERATIONS

<b>AQUATIC TOXICITY</b> (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).
<b>WASTE DISPOSAL METHOD:</b> IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

### SECTION XIV TRANSPORTATION INFORMATION

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	GROUND	NON-REGULATED	NON REGULATED	NON REGULATED	NA
IATA	AIR	NON REGULATED	NON REGULATED	NON REGULATED	NA
IMDG	OCEAN	NON REGULATED	NON REGULATED	NON REGULATED	NA
<b>MARINE POLLUTANT:</b>		THIS PRODUCT DOES CONTAIN A MATERIAL. ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B) (AR100)			

### SECTION XV REGULATORY INFORMATION

<b>TSCA:</b> THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6 (aromatic 100). or 1330-20-7 (xylenes)
<b>CERCLA:</b> IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675 <b>NO REPORTABLE SPILL QUANTITY (RQ) HAS BEEN ESTABLISHED FOR THIS PRODUCT (STODDARD SOLVENT, AROMATIC SOLVENT NAPHTHA).</b>
<b>SARA TITLE III:</b> UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: DELAYED HEALTH, FIRE
<b>ADDITIONAL REGULATORY CONCERNS:</b> (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)
FEDERAL / FDA / USDA:
<b>MARINE POLLUTANTS:</b> YES, THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B). SEE SECTION XIV
CERCLA / RQ: <b>NONE ESTABLISHED.</b> THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A):
<b>TSCA:</b> IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? <b>YES</b>

### SECTION XVI OTHER INFORMATION

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

### HMIS HAZARD RATINGS:

THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			<b>KEY</b>
<b>POWERCOAT ONE CLEAR</b>	<b>NPCA-HMIS</b>	<b>NFPA 704</b>	4 -- SEVERE
<b>HEALTH</b>	<b>1</b>	<b>1</b>	3 -- SERIOUS
<b>FLAMMABILITY</b>	<b>1</b>	<b>1</b>	2 -- MODERATE
<b>REACTIVITY</b>	<b>0</b>	<b>0</b>	1 -- SLIGHT
			0 -- MINIMAL