

HAZARD RATING  
 4=EXTREME  
 3=HIGH  
 2=MODERATE  
 1=SLIGHT  
 0=INSIGNIFICANT

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>

SAFETY DATA SHEET  
 VEXCON NO. CP100  
**POWERCOAT PRIMER WB**

**SECTION I - GENERAL INFORMATION**

<b>PRODUCT IDENTIFICATION:</b>	
<b>POERTCOAT PRIMER WB CLEAR &amp; PIGMENTED</b>	
<b>VOC CONTENT:</b>	<300 GRAMS/LITER OR <2.50 #/GAL
<b>CATEGORY:</b>	WATERPROOFING CONCRETE/MASONRY SEALER
<b>COMMON NAME:</b>	VINYLTOLUENE ACRYLATE EMULSION
<b>MANUFACTURER:</b>	<b>VEXCON CHEMICALS, INC</b>
<b>ADDRESS</b>	7240 STATE RD, PHILADELPHIA, PA 19135
<b>EMERGENCY NO:</b>	800.858.2828 (PolySat Inc)
<b>TELEPHONE NO:</b>	215.332.7709 (Vexcon)
<b>CHEMTREC NO:</b>	800.424.9300 (CCN# 23822)
<b>PREPARED:</b>	JANUARY 2001
<b>UPDATED:</b>	JULY 2020
<b>PREPARED BY:</b>	DARRY F. MANUEL , PRESIDENT

**SECTION II – HAZARD IDENTIFICATION**

<p><b>CLASSIFICATION OF MIXTURE</b>          ASPIRATION - CATEGORY 1          EYE IRRITATION – CATEGORY 2B          SKIN IRRITATION – CATEGORY 2          SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE (NARCOTIC EFFECTS) – CATEGORY 3</p> <p><b>SINGLE WORD:</b> WARNING</p> <p><b>HAZARD STATEMENT:</b> UNDER NORMAL CONDITIONS OF USE, THIS PRODUCT IS NOT CONSIDERED HAZARDOUS ACCORDING TO REGULATORY GUIDELINES.</p> <p><b>PRECAUTIONARY STATEMENT:</b> UNDER NORMAL CONDITIONS OF INTENDED USE, THIS PRODUCT DOES NOT POSE A RISK TO HEALTH. EXCESSIVE EXPOSURE MAY RESULT IN EYE, SKIN OR RESPIRATOR IRRITATION. THIS PRODUCT IS AN ORGANIC LIQUID AND WATER EMULSION. PER NFPA 30 THIS MIXTURE WITH A FLASH POINT GREATER THAN 200 F IS A CLASS III B COMBUSTIBLE LIQUID. ALL PRECAUTIONS PROVIDED ARE FOR THE ORGANIC LIQUID PORTION OF WHICH THIS PRODUCT MAY CONTAIN AS LITTLE AS 15%. USE WITH ADEQUATE VENTILATION. DO NOT INDUCE VOMITING IF SWALLOWED. USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT. <b>KEEP FROM FREEZING.</b></p>
---



**SECTION III HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
VINYLTOLUENE ACRYLATE POLYMER	25085-34-1	25-35%	ND	1993 (FLAMMABLE LIQUIDS, N.O.S)
SOLVENT NAPHTHA (Petroleum), LIGHT AROMATIC (AROMATIC 100)	64742-95-6	5-15%	TLV 50ppm OSHA HAZARD: COMBUSTIBL E LIQUID EXXON/MOBIL RCP 19ppm (TWA)	1268 (PETROLEUM DISTILLATES, N.O.S.)
PERFORMANCE ADDITIVES	NA	<5%	ND	NONE
WATER	7732-18-5	BALANCE	ND	NONE
<b>PIGMENTS</b>				
1.TITANIUM DIOXIDE (TiO2)	1363-67-1		OSHA PEL: 15mg/m (total dust) ACGIH TLV: 15mg/m (total dust)	
2. CALCIUM CARBONATE	1317-65-3		OSHA TWA 5.0 mg/m3 RESP. OSHA TWA 15.0 mg/m3 TOTAL	
<b>(AR100)THE AROMATIC SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:</b>				
COMPONENT	CAS NO.	MAX %	HAZARD DATA	UN#
1,2,4-TRIMETHYL BENZENE (PSEUDOCUMENE)	95-63-6	<32.0%	OSHA PEL: NE ACGIH TLV: 25ppm (TWA)	1993 (FLAMMABLE LIQUIDS, N.O.S) OR 3295 (HYDROCARBONS, LIQUID, N.O.S.)
XYLENES	1330-20-7	<2.2%	OSHA Z1 100ppm (TWA) ACGIH TLV 100ppm (TWA) NIOSH REL 100 ppm (TWA)	1307 (XYLENES)
CUMENE	98-82-8	<1.1%	OSHA Z1 50ppm (TWA) ACGIH TLV 50ppm (TWA)	1918 (ISOPROPYL BENZENE)
<b>(XYLENE) THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:</b>				
XYLENES	1330-20-7	70-80% TYPICAL	OSHA Z1 100ppm (TWA) ACGIH TLV 100ppm (TWA) NIOSH REL 100 ppm (TWA)	1307
ETHYL BENZENE	100-41-4	20-30% TYPICAL	OSHA Z1 100ppm (TWA) ACGIH TLV 100ppm (TWA) NIOSH REL 100 ppm (TWA)	1175

**SECTION IV FIRST AID MEASURES**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION  
BASIS FOR CLASSIFICATION SOURCE**

<b>ROUTES OF EXPOSURE:</b>	
<b>INHALATION:</b>	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. VAPOR INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA OR HEADACHE. AROMATIC SOLVENT COMPONENT
<b>SKIN CONTACT:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC SOLVENT COMPONENT.
<b>SKIN ABSORPTION:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC SOLVENT COMPONENT.
<b>EYE CONTACT:</b>	THIS PRODUCT MAY BE AN EYE IRRITANT. AROMATIC SOLVENT COMPONENT.
<b>INGESTION / INHALATION</b>	CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>EFFECTS OF OVEREXPOSURE:</b>	<b>TLV 50 ppm AR-100</b> ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
<b>ACUTE OVEREXPOSURE:</b>	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.
<b>EMERGENCY AND FIRST AID PROCEDURES:</b>	
<b>EYES:</b>	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION. CONSULT A PHYSICIAN.
<b>SKIN:</b>	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
<b>INHALATION:</b>	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
<b>INGESTION:</b>	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

**SECTION V FIREFIGHTING MEASURES**

<b>EXTINGUISHING MEDIA:</b>	EXCLUDE AIR. FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY <b>REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY.</b> WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER.
<b>GENERAL HAZARD:</b>	<b>FLAMMABLE</b> - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. <b>STATIC DISCHARGE</b> - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. <b>"EMPTY" CONTAINERS</b> RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
<b>ELECTRO-STATIC ACCUMULATION HAZARD:</b>	<u><b>USE PROPER GROUNDING</b></u>
<b>UNUSUAL FIRE AND EXPLOSION HAZARD:</b>	PRODUCT WILL BURN IF TEMPERATURE EXCEEDS BOILING POINT. WATER MIX: NO UNUSUAL HAZARDS.

**SPECIAL FIRE FIGHTING PROCEDURES**

THE USE OF **SELF-CONTAINED BREATHING APPARATUS** WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED.  
STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP.  
USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE.  
AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

**SECTION VI ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** ELIMINATE SOURCES OF IGNITION (FLARES, FLAMES, PILOT LIGHTS, ELECTRICAL SPARKS). PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. DIKE SPILL AREA WITH SAND OR EARTH TO CONTAIN SPILLED LIQUID AND PREVENT SPREADING. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR WITH ANOTHER SUITABLE ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

**SECTION VII HANDLING AND STORAGE**

**PRECAUTIONARY STATEMENTS:** PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**FIRE FIGHTING:** WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINERS COOL, DRY, AND AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

**SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION**

**VENTILATION REQUIREMENTS:** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

**EYES:** CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

**GLOVES:** THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

**OTHER CLOTHING AND EQUIPMENT:** TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

**SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS**

<b>BOILING POINT: (760mmHg)</b> 100°C / 212°F (WATER)	<b>MELTING/FREEZING POINT:</b> 0°C / 32°F (WATER)
<b>VAPOR PRESSURE:</b> 1.97 mmHg@68°F/20°C (AR100)	<b>VAPOR DENSITY (AIR=1):</b> 4.2 (AR100)
<b>SOLUBILITY IN H2O % BY WT:</b> 100%	<b>% VOLATILES BY VOL:</b> 70-80%
<b>EVAPORATION RATE (BuAc=1):</b> 0.27 SLOW (AR100)	<b>REALITIVE DENSITY (H2O=1)</b> 1.002
<b>pH (AS IS):</b> N/A	<b>pH (1% SOLN):</b> N/A
<b>APPEARANCE AND ODOR:</b> MILKY WHITE EMULSION WITH AROMATIC SOLVENT ODOR	
<b>FLASH POINT:</b> (TEST METHOD)	<b>&lt;93°C / &lt;200°F (TCC)</b>
<b>AUTOIGNITION TEMP:</b>	479°C / 894°F (AR100)
<b>FLAMMABLE LIMITS IN AIR, % BY VOL:</b>	LOWER: 0.9% UPPER: 6.2% (AR100)

**SECTION X STABILITY AND REACTIVITY**

<b>CONDITIONS CONTRIBUTING TO INSTABILITY:</b>	THIS PRODUCT IS STABLE.
<b>INCOMPATIBILITY:</b>	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
<b>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:</b>	N/A WILL NOT OCCUR

**SECTION XI TOXICOLOGICAL INFORMATION**

ROUTE OF EXPOSURE	CONCLUSION/REMARKS	
<b>INHALATION</b>	TOXICITY	MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. BASED ON TEST DATA FOR THE MATERIAL
	IRRITATION	MAY BE IRRITATING TO THE RESPIRATORY TRACT. THE EFFECTS ARE REVERSIBLE. BASED ON TEST DATA FOR STRUCTURALLY SIMILAR MATERIALS.
<b>INGESTION</b>	TOXICITY: LD50 >3000 mg/kg	MINIMALLY TOXIC. BASED ON TEST FOR STRUCTURALLY SIMILAR MATERIALS
<b>SKIN</b>	TOXICITY LD50 >3160 mg/kg	MINIMALLY TOXIC . BASED ON TEST DATA FOR THE MATERIAL
	IRRITATION	MILDLY IRRITATING TO SKIN WITH PROLONGED EXPOSURE. BASED ON THEST DATA FOR THE MATERIAL
<b>EYE</b>	IRRITATION	MAY CAUSE MILD, SHORT-LASTING DISCOMFORT TO EYES. BASED ON TEST DATA FOR THE MATERIAL.
<b>CHRONIC/OTHER EFFECTS</b>	VAPOR/AEROSOL CONCENTRATIONS ABOVE RECOMMENDED EXPOSURE LEVELS ARE IRRITATING TO THE EYES AND RESPIRATORY TRACT, MAY CAUSE HEADACHES, SIZZINESS, ANESTHESIA, DROWINESS, UNCONSCIOUSNESS AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DEATH.	
	PROLONGED AND/OR REPEATED SKIN CONTACT WITH LOW VISCOSICY MATERIALS MAY DEFAT THE SKIN RESULTING IN POSSIBLE IRRITATION AND DERMATITIS.	
	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE LUNGS DURING INGESTION OF FROM VOMITING MAY CAUSE CHEMICAL PNEUMONITIS OR PULMONARY	

	EDEMA.
CONTAINS CUMENE	REPEATED INHALATION EXPOSURE OF CUMENE VAPOR PRODUCED DAMAGES IN THE KIDNEY OF MALE RATS ONLY. THESE EFFECTS ARE BELIEVED TO BE SPECIES SPECIFIC AND ARE NOT RELEVANT TO HUMANS.

**SECTION XII ECOLOGICAL INFORMATION**

<b>THE INFORMATION GIVEN IS BASED ON DATA AVAILABLE FOR THE MATERIAL, THE COMPONENTS OF THE MATERIAL, AND SIMILAR MATERIALS.</b>	
<b>ECOTOXICITY</b>	MATERIAL – EXPECTED TO BE TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>MOBILITY</b>	MATERAIL – HIGHLY VOLATILE, WILL PARTITION RAPIDLY TO AIR. NOT EXPECTED TO PARTITION TO SEDIMENT AND WASTEWATER SOLIDS.
<b>PRESISTENCE AND DEGRADABILITY</b>	
<b>BIODEGRADATION</b>	MATERIAL – EXPECTED TO READILY BIODEGRADABLE.
<b>HYDROLYSIS</b>	MATERIAL- TRANSFORMATION DUE TO HYDROLYSIS NO EXPECTED OT BE SIGNIFICANT.
<b>PHOTOLYSIS</b>	MATERIAL – TRANSFORMATION DUE TO PHOTOLYSIS NOT EXPECTED TO BE SIGNIFICANT.
<b>ATMOSPHERIS OXIDATION</b>	MATERIAL – EXPECTED TO DEGRADE RAPIDLY IN AIR.

**SECTION XIII DISPOSAL CONSIDERATIONS**

<b>AQUATIC TOXICITY (EG 96HR TLM):</b> DO NOT DISCHARGE THIS PRODUCT INTO PUBLIS WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATAION SYSTEM (NPDES) ERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA)
<b>WASTE DISPOSAL METHOD:</b> IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT, TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

**SECTION XIV TRANSPORTATION INFORMATION**

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	GROUND	NON REGULATED	NON REGULATED	NON REGULATED	NA
IATA	AIR	NON REGULATED	NON REGULATED	NON REGULATED	NA
IMDG	OCEAN	NON REGULATED	NON REGULATED	NON REGULATED	NA
<b>MARINE POLLUTANT:</b>	THIS PRODUCT DOES CONTAIN A MATERIAL. ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B) AROMATIC 100				

**SECTION XV REGULATORY INFORMATION**

<b>TSCA:</b> THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6 (aromatic 100).
<b>CERCLA:</b> IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675. <b>NO REPORTABLE SPILL QUANTITY (RQ) HAS BEEN ESTABLISHED FOR THIS PRODUCT (STODDARD SOLVENT, AROMATIC SOLVENT NAPHTHA).</b>
<b>SARA TITLE III:</b> UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: DELAYED HEALTH, FIRE
<b>ADDITIONAL REGULATORY CONCERNS:</b> (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)
FEDERAL / FDA / USDA:
<b>MARINE POLLUTANTS:</b> YES THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B). SEE SECTION XIV
<b>CALIFORNIA PROP 65:</b> WARNING: This product contains chemicals known to the state of California to cause cancer or birth defects or other reproductive harm. (Epichlorohydrin, Ethylbenzene, Crystalline Silica particles of respirable size)
<b>CERCLA / RQ:</b> <b>NONE ESTABLISHED.</b> THIS PRODUCT CONTAINS A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A): XYLENES, MIXED
<b>TSCA:</b> IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? <b>YES</b>

**SECTION XVI OTHER INFORMATION**

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

<b>HMIS HAZARD RATINGS:</b>		<b>KEY</b> 4 -- SEVERE
THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS		
<b>POWERCOAT PRIMER WB CLEAR &amp; PIGMENTED</b>	<b>NPCA- HMIS</b>	<b>NFPA 704</b>
<b>HEALTH</b>	<b>1</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>	<b>0</b>
		3 -- SERIOUS
		2 -- MODERATE
		1 -- SLIGHT
		0 -- MINIMAL